

APC Basic Rack-Mount PDU - power distribution strip - 2.3 kW



Not in stock

SKU	AP9568
Product Description:	APC Basic Rack-Mount PDU - power distribution strip - 2.3 kW
Device Type:	Power distribution strip - rack-mountable
Cord Length:	1.98 m
Weight:	2 kg
Input Voltage:	AC 208/230 V
Output Voltage:	AC 208/230 V
Power Capacity:	2.3 kW

General

Device Type:	Power distribution strip - rack-mountable
Cord Length:	1.98 m
Colour:	Black

Power Device

Input Voltage:	AC 208/230 V
Input Voltage Range:	AC 200 - 240 V
Frequency Provided:	50/60 Hz
Frequency Required:	50/60 Hz
Input Connectors:	1 x power IEC 60320 C14
Power Output Connectors Details:	15 x power IEC 60320 C13
Output Voltage:	AC 208/230 V 50/60 Hz
Max Electric Current:	10 A
Power Capacity:	2.3 kW

Miscellaneous

Cables Included:	Power cable - external - 1.98 m
Rack Mounting Kit:	Included
Compliant Standards:	UL, cUL, VDE

Manufacturer Warranty

Compatibility Information

P/N:	AR2487G, AR3100W, AR3103SP, AR3105SP, AR3105W, AR3106SP, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR3357X674, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, NBPDO160A, NBWLO355A, NBWLO356A, SCL500RMI1UC, SCL500RMI1UNC, SMC1000-BR, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC1500I-2UC, SMC1500I-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I, SMC2000I-2U, SMC3000I, SMT1000I-6W, SMT1000I-AR, SMT1000IC, SMT1000R2I-AR, SMT1000RMI2UC, SMT1500I-AR, SMT1500IC, SMT1500R2I-6W, SMT1500R2I-AR, SMT1500RMI2UC, SMT1500RMI2UNC, SMT2200I-AR, SMT2200IC, SMT2200R2I-AR, SMT2200RMI2UC, SMT2200RMI2UNC, SMT2200RMI2UNC, SMT3000I-2U-BR, SMT3000I-AR, SMT3000IC, SMT3000R2I-6W, SMT3000R2I-AR, SMT3000RMI2UC, SMT3000RMI2UNC, SMT750RMI2UC, SMT750RMI2UNC, SMTL750RMI2UC, SMX1000C, SMX1000US, SMX1500RMI2UC, SMX1500RMI2UNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LVNCUS, SMX2000LVUS, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMLVUS, SMX3000HV-BR, SMX3000HVTUS, SMX3000LV2U-BR,
------	---

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 2 years ; Limited warranty - replacement - 2 years
--------------------	---

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Min Storage Temperature:	-25 °C
Max Storage Temperature:	65 °C
Humidity Range Operating:	5 - 95%
Humidity Range Storage:	5 - 95%

Dimensions & Weight

Width:	4.5 cm
Depth:	4.5 cm
Height:	61 cm
Weight:	2 kg

Compatibility Information

SMX3000LVNCUS, SMX3000LVUS,
SMX3000RMLVUS, SMX3KRMLVNCUS,
SMX750C, SMX750CNC, SMX750INC,
SMX750US, SPD10KCBL, SPD20KCBL,
SRC2000XLI-CC, SRC3KUXI, SRT1000RMXLA,
SRT1000RMXLA-NC, SRT1000RMXLI,
SRT1000RMXLI-NC, SRT10KRMXLT-IEC,
SRT10KXLT-IEC, SRT10RMXLIX806,
SRT1500RMXLA, SRT1500RMXLA-NC,
SRT1500RMXLI, SRT1500XLI,
SRT2200RMXLI, SRT2200RMXLI-NC,
SRT2200XLI, SRT2200XLI-KR,
SRT3000RMXLI, SRT3000RMXLI-NC,
SRT3000RMXLW-IEC, SRT3000XLI,
SRT3000XLW-IEC, SRT5KRMXLI-6W,
SRT5KRMXLIM, SRT5KRMXLT-IEC,
SRT5KRMXLTUS, SRT5KRMXLW-TW,
SRT6KRMXLI-6W, SRT6KRMXLIM,
SRT6KRMXLT-IEC, SRT6KXLT-IEC,
SRT8KRMXLT-IEC, SRT8KXLT-IEC,
SUA1000ICH-45, SUA1500I-IN, SUA2200ICH-
45, SUA3000I-IN, SURT1000RMXLI-NC,
SURT1000XLI-NC, SYAF16KRMICH

