

APC Basic Rack-Mount PDU - power distribution strip - 3680 Watt



SKU	AP7552
Product Description:	APC Basic Rack-Mount PDU - power distribution strip - 3680 Watt
Device Type:	Power distribution strip - rack-mountable
Cord Length:	3.05 m
Weight:	4.9 kg
Input Voltage:	AC 230 V
Output Voltage:	AC 230 V
Power Capacity:	3680 Watt

General

Device Type:	Power distribution strip - rack-mountable
Cord Length:	3.05 m
Colour:	Black

Power Device

Input Voltage:	AC 230 V
Frequency Provided:	50/60 Hz
Frequency Required:	50/60 Hz
Input Connectors:	1 x power IEC 60320 C20
Power Output Connectors Details:	20 x power IEC 60320 C13 ; 4 x power IEC 60320 C19
Output Voltage:	AC 230 V 50/60 Hz
Max Electric Current:	16 A
Power Capacity:	3680 Watt

Miscellaneous

Cables Included:	Power cable - external - 3.05 m
Rack Mounting Kit:	Included
Compliant Standards:	EN 60950, VDE

Compatibility Information

P/N:	AP6221CH, AR2200, AR2280, AR2487G, AR3100G, AR3100TAA, AR3100W, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3180G, AR3300G, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR3357X674, DLT3000RMI2U, NBE50302, NBPDO160A, NBPDO180, NBWL0355A, NBWL0356A, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I, SMC2000I-2U, SMC3000I, SMC3000RMI2U, SMT1500RMI1U, SMT1500RMI1U, SMT2200I-AR, SMT2200IC, SMT2200R2I-AR, SMT2200RM2UC, SMT2200RMI2UC, SMT2200RMI2UNC, SMT3000I2U-BR, SMT3000I-AR, SMT3000IC, SMT3000R2I-6W, SMT3000R2I-AR, SMT3000RM2UC, SMT3000RMI2UC, SMT3000RMI2UNC, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LVNC, SMX2000LVNCUS, SMX2000LVUS, SMX2200HV, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMI2UC, SMX2200RMLVUS, SMX3000HV, SMX3000HV-BR, SMX3000HVNC, SMX3000HVT, SMX3000HVTUS,
------	--

Manufacturer Warranty

Manufacturer Warranty

Service & Support:	Limited warranty - parts and labour - 2 years
	Limited warranty - replacement - 2 years

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Min Storage Temperature:	-25 °C
Max Storage Temperature:	65 °C
Humidity Range Operating:	5 - 95%
Humidity Range Storage:	5 - 95%

Dimensions & Weight

Width:	5.6 cm
Depth:	4.4 cm
Height:	161.9 cm
Weight:	4.9 kg

Compatibility Information

SMX3000LV, SMX3000LV2U-BR,
SMX3000LVNCUS, SMX3000LVUS,
SMX3000RMLVUS, SMX3KRMLVNCUS,
SMX750C, SMX750CNC, SMX750US,
SPD10KCBL, SPD20KCBL, SRT1000RMXLA,
SRT1000RMXLA-NC, SRT1000RMXLI,
SRT1000RMXLI-NC, SRT10KRMXLI,
SRT10KRMXLT-IEC, SRT10KXLI, SRT10KXLT-IEC,
SRT10RMXLIX806, SRT1500RMXLA,
SRT1500RMXLA-NC, SRT1500XLI,
SRT2200RMXLI, SRT2200RMXLI-NC,
SRT2200XLI, SRT2200XLI-KR,
SRT3000RMXLI, SRT3000RMXLI-NC,
SRT3000RMXLW-IEC, SRT3000XLI,
SRT3000XLW-IEC, SRT5KRMXLI,
SRT5KRMXLI-6W, SRT5KRMXLIM,
SRT5KRMXLT, SRT5KRMXLT-IEC,
SRT5KRMXLTUS, SRT5KRMXLW-HW,
SRT5KRMXLW-TW, SRT5KXLI, SRT6KRMXLI,
SRT6KRMXLI-6W, SRT6KRMXLIM,
SRT6KRMXLT, SRT6KRMXLT-IEC, SRT6KXLI,
SRT6KXLT-IEC, SRT8KRMXLI, SRT8KRMXLT,
SRT8KRMXLT-IEC, SRT8KXLI, SRT8KXLT-IEC,
SUA2200ICH-45, SUA3000ICH-45,
SUA3000I-IN, SURT3000XLI-ET,
SURT5000XLIX438, SURTD3000RMXLI-CC,
SURTD5000XLI-ET, SYAF16KRMICH