

APC Basic Rack-Mount PDU - power distribution strip



In Stock(5)

SKU	AP9565
Product Description:	APC Basic Rack-Mount PDU - power distribution strip
Device Type:	Power distribution strip - rack-mountable
Cord Length:	2.5 m
Rack Size:	19" - 1U
Weight:	2 kg
Localisation:	Belgium, Bahrain, Jordan, Lebanon, United Arab Emirates, Albania, Argentina, Australia, Bulgaria, China, Colombia, Czech Republic, Estonia, Indonesia, Israel, Lithuania, South Africa, Vietnam, Ukraine, Venezuela, Canada, Chile, Egypt, Hong Kong, Mexico, New Zealand, Pakistan, Romania, Thailand, Malaysia, Singapore, Puerto Rico, Luxembourg, Hungary, India, Kenya, Nigeria, Uganda, Tanzania, Bolivia, Uruguay, Peru, Paraguay, Ecuador, Honduras, Guatemala, Costa Rica, Salvador, Panama, Nicaragua, Dominican Republic, Trinidad, Jamaica, Ethiopia, Somalia, Rwanda, Zimbabwe, Philippines, Yugoslavia, Bosnia, Croatia, Macedonia, Slovenia, Korea, Latvia, Herzegovina, Burundi, Djibouti, Netherlands Antilles, Austria, Brazil, Denmark, Finland, France, Germany, Italy, Netherlands, Norway, Poland, Portugal, Russia, Spain, Sweden, Switzerland, United Kingdom, United States, Greece, Turkey, Ireland
Input Voltage:	AC 208/230 V

General

Device Type:	Power distribution strip - rack-mountable
Height (Rack Units):	1U
Rack Size:	19"
Cord Length:	2.5 m
Colour:	Black

Compatibility Information

P/N: AR106, AR106SH4, AR106SH6, AR109SH4, AR109SH6, AR112, AR112SH4, AR112SH6, AR2487G, AR3003, AR3003SP, AR3006, AR3006SP, AR3100W, AR3103, AR3103SP, AR3105SP, AR3105W, AR3106, AR3106SP, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR3357X674, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, AR8213, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBPD0160A, NBWL0355A, NBWL0356A,

General

Localisation:

Belgium, Bahrain, Jordan, Lebanon, United Arab Emirates, Albania, Argentina, Australia, Bulgaria, China, Colombia, Czech Republic, Estonia, Indonesia, Israel, Lithuania, South Africa, Vietnam, Ukraine, Venezuela, Canada, Chile, Egypt, Hong Kong, Mexico, New Zealand, Pakistan, Romania, Thailand, Malaysia, Singapore, Puerto Rico, Luxembourg, Hungary, India, Kenya, Nigeria, Uganda, Tanzania, Bolivia, Uruguay, Peru, Paraguay, Ecuador, Honduras, Guatemala, Costa Rica, Salvador, Panama, Nicaragua, Dominican Republic, Trinidad, Jamaica, Ethiopia, Somalia, Rwanda, Zimbabwe, Philippines, Yugoslavia, Bosnia, Croatia, Macedonia, Slovenia, Korea, Latvia, Herzegovina, Burundi, Djibouti, Netherlands Antilles, Austria, Brazil, Denmark, Finland, France, Germany, Italy, Netherlands, Norway, Poland, Portugal, Russia, Spain, Sweden, Switzerland, United Kingdom, United States, Greece, Turkey, Ireland

Power Device

Input Voltage:	AC 208/230 V
Frequency Provided:	50/60 Hz
Frequency Required:	50/60 Hz
Input Connectors:	1 x power IEC 60320 C20
Power Output Connectors Details:	12 x power IEC 60320 C13
Output Voltage:	AC 208/230 V 50/60 Hz
Max Electric Current:	16 A

Miscellaneous

Cables Included:	Power cable - integrated - 2.5 m
Rack Mounting Kit:	Included
Compliant Standards:	UL, cUL, UL 1363

Manufacturer Warranty

Compatibility Information

Designed For:

SCL400RMJ1U, SCL500RM1UC, SCL500RM1UNC, SCL500RM1UC, SCL500RM1UNC, SMC1000-BR, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I, SMC2000I-2U, SMC3000I, SMT2200I-AR, SMT2200IC, SMT2200R2I-AR, SMT2200RM2UC, SMT2200RM2UC, SMT2200RM2UNC, SMT3000I2U-BR, SMT3000I-AR, SMT3000IC, SMT3000R2I-6W, SMT3000R2I-AR, SMT3000RM2UC, SMT3000RM2UC, SMT3000RM2UNC, SMTL1000RM2UC, SMTL1000RM2UC, SMTL750RM2UC, SMTL750RM2UC, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LVNCUS, SMX2000LVUS, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMLVUS, SMX3000HV-BR, SMX3000HVTUS, SMX3000LV2U-BR, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750C, SMX750CNC, SMX750US, SPD10KCB, SPD20KCB, SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT1000RMXLI-NC, SRT10KRMXLT-IEC, SRT10KXLT-IEC, SRT10RMXLIX806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT1500XLI, SRT2200RMXLI, SRT2200RMXLI-NC, SRT2200XLI, SRT2200XLI-KR, SRT3000RMXLI, SRT3000RMXLI-NC, SRT3000RMXLW-IEC, SRT3000XLI, SRT3000XLW-IEC, SRT5KRMXLI-6W, SRT5KRMXLIM, SRT5KRMXLT, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-TW, SRT6KRMXLI-6W, SRT6KRMXLIM, SRT6KRMXLT, SRT6KRMXLT-IEC, SRT6KXLT-IEC, SRT8KRMXLT, SRT8KRMXLT-IEC, SRT8KXLT-IEC, SUA2200ICH-45, SUA3000I-IN, SYAF16KRMICH

Dimensions & Weight

Width:	44.7 cm
Depth:	5.7 cm
Height:	4.5 cm
Weight:	2 kg

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C

Manufacturer Warranty

Service & Support: Limited warranty - parts and labour - 2 years

Environmental Parameters

Min Storage Temperature:	-25 °C
Max Storage Temperature:	65 °C
Humidity Range Operating:	0 - 95%
Humidity Range Storage:	0 - 95%

