

APC Basic Rack PDU AP6020A - power distribution unit



In Stock(4)

SKU	AP6020A
Product Description:	APC Basic Rack PDU AP6020A - power distribution unit
Device Type:	Power distribution unit - rack-mountable
Weight:	1.5 kg
Input Voltage:	AC 100-240 V
Output Voltage:	AC 100-240 V + 6% / - 10%
Input Connectors:	1 x power IEC 60320 C20
Output connectors:	13 x power IEC 60320 C13

General

Device Type: Power distribution unit - rack-mountable

Power Device

Input Voltage:	AC 100-240 V
Frequency Required:	50/60 Hz
Input Connectors:	1 x power IEC 60320 C20
Power Output Connectors Details:	13 x power IEC 60320 C13
Output Voltage:	AC 100-240 V + 6% / - 10%
Max Electric Current:	20 A

Miscellaneous

Compliant Standards: UL, VDE, RoHS 2011/65/EU

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	5 - 95% (non-condensing)

Dimensions & Weight

Compatibility Information

P/N: AP7950B, AR106, AR112, AR2200, AR2280, AR2487G, AR3100TAA, AR3100W, AR3103SP, AR3105SP, AR3105W, AR3106SP, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR4000MVX429, AR4000MVX432, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, AR8213, NBPD0160A, NBWLO355A, NBWLO356A, SCL400RM1IU, SCL500RM1UC, SCL500RM1UNC, SCL500RM1IUC, SMC1000-BR, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I, SMC2000I-2U, SMC3000I, SMC3000RM12U, SMT2200I-AR, SMT2200IC, SMT2200R2I-AR, SMT2200RM2UC, SMT2200RM12UC, SMT2200RM12UNC, SMT3000I2U-BR, SMT3000I-AR, SMT3000IC, SMT3000R2I-6W, SMT3000R2I-AR, SMT3000RM2UC, SMT3000RM12UC, SMT3000RM12UNC, SMTL1000RM2UC, SMTL1000RM12UC, SMTL750RM2UC, SMTL750RM12UC, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LVNCUS, SMX2000LVUS, SMX2200HVNC,

Dimensions & Weight

Width:	4.36 cm
Depth:	9.29 cm
Height:	38.81 cm
Weight:	1.5 kg

Dimensions & Weight (Shipping)

Shipping Width:	21.03 cm
Shipping Depth:	7.59 cm
Shipping Height:	43.61 cm
Shipping Weight:	2 kg

Compatibility Information

SMX2200R2HVNC, SMX2200RMLVUS,
SMX3000HV-BR, SMX3000HVTUS,
SMX3000LV2U-BR, SMX3000LVNCUS,
SMX3000LVUS, SMX3000RMLVUS,
SMX3KRMLVNCUS, SMX750C, SMX750CNC,
SMX750US, SRT1000RMXLA,
SRT1000RMXLA-NC, SRT1000RMXLI,
SRT1000RMXLI-NC, SRT10KRMXLI,
SRT10KRMXLT-IEC, SRT10KXLI, SRT10KXLT-IEC,
SRT10RMXLIX806, SRT1500RMXLA,
SRT1500RMXLA-NC, SRT2200RMXLI,
SRT2200RMXLI-NC, SRT2200XLI,
SRT3000RMXLI, SRT3000RMXLI-NC,
SRT3000RMXLW-IEC, SRT3000XLI,
SRT3000XLW-IEC, SRT5KRMXLI,
SRT5KRMXLI-6W, SRT5KRMXLIM,
SRT5KRMXLT, SRT5KRMXLT-IEC,
SRT5KRMXLTUS, SRT5KRMXLW-HW,
SRT5KRMXLW-TW, SRT6KRMXLI,
SRT6KRMXLI-6W, SRT6KRMXLIM,
SRT6KRMXLT, SRT6KRMXLT-IEC, SRT6KXLI,
SRT6KXLT-IEC, SRT8KRMXLI, SRT8KRMXLT,
SRT8KRMXLT-IEC, SRT8KXLI, SRT8KXLT-IEC,
SUA2200ICH-45, SUA3000ICH-45,
SUA3000I-IN, SURT5000XLIX438,
SYAF16KRMICH

