

APC Basic Rack PDU AP6032A - power distribution unit



In Stock(6)

SKU	AP6032A
Product Description:	APC Basic Rack PDU AP6032A - power distribution unit
Device Type:	Power distribution unit - rack-mountable
Cord Length:	3.65 m
Weight:	2.78 kg
Input Voltage:	AC 200-240 V
Output Voltage:	AC 200-240 V + 6% / - 10%
Input Connectors:	1 x power IEC 60309 32A

General

Device Type:	Power distribution unit - rack-mountable
Cord Length:	3.65 m

Power Device

Input Voltage:	AC 200-240 V
Input Voltage Margin:	+ 6% / - 10%
Frequency Required:	50/60 Hz
Input Connectors:	1 x power IEC 60309 32A
Power Output Connectors Details:	4 x power IEC 60320 C19 16A
Output Voltage:	AC 200-240 V + 6% / - 10%
Max Electric Current:	32 A

Miscellaneous

Cables Included:	Power cable - integrated - 3.65 m
Features:	Breaker protection, over current protection
Compliant Standards:	UL, VDE, RoHS 2011/65/EU

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	50 °C

Compatibility Information

P/N:	ACDC2513, AP7950B, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3100G, AR3100TAA, AR3100W, AR3103SP, AR3105SP, AR3105W, AR3106SP, AR3107G, AR3107SP, AR3107X609, AR3140G, AR3140W, AR3150SP, AR3150W, AR3150X610, AR3150X617, AR3155SP, AR3155W, AR3157SP, AR3157X617, AR3180G, AR3300G, AR3300SP, AR3300W, AR3300X610, AR3300X617, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3340G, AR3340W, AR3350SP, AR3350W, AR3350X610, AR3350X617, AR3355SP, AR3355W, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, AR4018A, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X432, AR4024A, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038A, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, NBES0302, NBPDO160A, NBPDO180, NBWL0355A, NBWL0356A, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RM12U, SMT1500RM1U, SMT1500RM2U, SMT1500RM11U, SMT2200RM2UC, SMT3000I2U-BR,
------	--

Environmental Parameters

Humidity Range Operating:	5 - 95% (non-condensing)
---------------------------	--------------------------

Dimensions & Weight

Width:	4.36 cm
Depth:	9.29 cm
Height:	43.81 cm
Weight:	2.78 kg

Dimensions & Weight (Shipping)

Shipping Width:	20.8 cm
Shipping Depth:	18 cm
Shipping Height:	47.8 cm
Shipping Weight:	3.75 kg

Compatibility Information

SMT3000RM2UC, SMX1000US, SMX1500RMNCUS, SMX1500RMUS, SMX2000LV, SMX2000LVNC, SMX2000LVNCUS, SMX2000LVUS, SMX2200HV, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMHV2U, SMX2200RMLVUS, SMX3000HV, SMX3000HV-BR, SMX3000HVNC, SMX3000HVT, SMX3000HVTUS, SMX3000LV, SMX3000LV2U-BR, SMX3000LVNC, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750-NMC, SMX750US, SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT1000RMXLI-NC, SRT10KRMXLI, SRT10RMXLIX806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT5KRMXLT, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-HW, SRT5KRMXLW-TW, SRT6KRMXLI, SRT6KRMXLT, SRT6KRMXLT-IEC, SRT8KRMXLI, SRT8KRMXLT, SRT8KRMXLT-IEC, SURT3000XLI-ET, SURT5000XLIX438, SYAF16KRMICH

