

APC Basic Rack PDU - power distribution strip



Not in stock

SKU	AP7586
Product Description:	APC Basic Rack PDU - power distribution strip
Device Type:	Power distribution strip - rack-mountable
Cord Length:	8.5 m
Rack Size:	19" - 2U
Weight:	4 kg
Input Voltage:	AC 230 V
Output Voltage:	AC 230 V

General

Device Type:	Power distribution strip - rack-mountable
Height (Rack Units):	2U
Rack Size:	19"
Cord Length:	8.5 m
Colour:	Black

Power Device

Input Voltage:	AC 230 V
Frequency Required:	50/60 Hz
Input Connectors:	Hardwire
Power Output Connectors Details:	4 x power IEC 60309
Output Voltage:	AC 230 V
Max Electric Current:	32 A

Miscellaneous

Cables Included:	Power cable - integrated - 8.5 m
Rack Mounting Kit:	Included
Compliant Standards:	VDE

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Compatibility Information

P/N:	ACDC2513, AR106, AR112, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3100G, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3107X609, AR3107X617, AR3140G, AR3140W, AR3150SP, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155SP, AR3155W, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340G, AR3340W, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355SP, AR3355W, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR8213, NBES0302, NBPDO160A, NBPDO180, NBWLO355A, NBWLO356A, SCL400RM11U, SCL500RM1UC, SCL500RM1UNC, SCL500RM11UC, SCL500RM11UNC, SMC1000, SMC1000-2U, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC1500, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RM12U, SMT1500RM1U, SMT1500RM2U, SMT1500RM11U, SMT2200RM2UC, SMT3000I2U-BR, SMT3000RM2UC, SMTL1000RM2UC, SMTL1000RM12UC, SMTL750RM2UC, SMTL750RM12UC, SMX1000US, SMX1500RMNCUS, SMX1500RMUS,
------	---

Designed For:

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	0 - 95%

Dimensions & Weight

Width:	43.7 cm
Depth:	8.9 cm
Height:	8.9 cm
Weight:	4 kg

Compatibility Information

SMX2000LV, SMX2000LVNC,
SMX2000LVNCUS, SMX2000LVUS,
SMX2200HV, SMX2200HVNC,
SMX2200R2HVNC, SMX2200RMHV2U,
SMX2200RMLVUS, SMX3000HV,
SMX3000HV-BR, SMX3000HVNC,
SMX3000HVT, SMX3000HVTUS,
SMX3000LV, SMX3000LV2U-BR,
SMX3000LVNC, SMX3000LVNCUS,
SMX3000LVUS, SMX3000RMLVUS,
SMX3KRMLVNCUS, SMX750-NMC,
SMX750US, SRT1000RMXLA,
SRT1000RMXLA-NC, SRT1000RMXLI,
SRT1000RMXLI-NC, SRT10KRMXLI,
SRT10RMXLIX806, SRT1500RMXLA,
SRT1500RMXLA-NC, SRT5KRMXLT,
SRT5KRMXLT-IEC, SRT5KRMXLTUS,
SRT5KRMXLW-HW, SRT5KRMXLW-TW,
SRT6KRMXLI, SRT6KRMXLT, SRT6KRMXLT-
IEC, SRT8KRMXLI, SRT8KRMXLT,
SRT8KRMXLT-IEC, SURT3000XLI-ET,
SURT5000XLI438, SURTD5000XLI-ET,
SYA12K16ICH, SYA12K16IXRCH,
SYA12K16RMICH, SYA16K16IXRCH,
SYA8K16ICH, SYAF16KRMICH

