

APC Basic Rack PDU Zero U - power distribution panel



SKU	AP7554
Product Description:	APC Basic Rack PDU Zero U - power distribution panel
Device Type:	Power distribution panel - rack-mountable
Rack Size:	0U
Weight:	5.6 kg
Input Voltage:	AC 230 V
Output Voltage:	AC 230 V
Input Connectors:	1 x power IEC 60309

General

Device Type:	Power distribution panel - rack-mountable
Height (Rack Units):	0U
Colour:	Black

Power Device

Input Voltage:	AC 230 V
Frequency Required:	47 - 63 Hz
Input Connectors:	1 x power IEC 60309
Power Output Connectors Details:	20 x power IEC 60320 C13 ; 4 x power IEC 60320 C19
Output Voltage:	AC 230 V
Max Electric Current:	16 A

Miscellaneous

Cables Included:	Power cable - integrated - 3.1 m
Rack Mounting Kit:	Included
Compliant Standards:	EN 60950, VDE, IEC 60950

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Environmental Parameters

Min Operating Temperature:	-5 °C
----------------------------	-------

Compatibility Information

P/N: AP5607, AP6351CH, AP6451CH, AP7950B, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3100G, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3105, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140G, AR3140W, AR3150SP, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, NBES0302, NBPDO160A, NBPDO171, NBPDO172, NBPDO180, NBWL0355A, NBWL0356A, SMC1000, SMC1000-2U, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC1500, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RMI2U, SMT1500RM1U, SMT1500RM2U, SMT1500RM11U, SMT2200RM2UC, SMT3000I2U-BR, SMT3000RM2UC, SMT3000RMT2U, SMX1000U5, SMX1500RMNCUS, SMX1500RMUS, SMX2000LV, SMX2000LVNC, SMX2000LVNCUS,

Designed For:

Environmental Parameters

Max Operating Temperature:	45 °C
Humidity Range Operating:	5 - 95%

Dimensions & Weight

Width:	5.6 cm
Depth:	4.4 cm
Height:	162 cm
Weight:	5.6 kg

Compatibility Information

SMX2000LVUS, SMX2200HV,
SMX2200HVNC, SMX2200R2HVNC,
SMX2200RMHV2U, SMX2200RMLVUS,
SMX3000HV, SMX3000HV-BR,
SMX3000HVNC, SMX3000HVT,
SMX3000HVTUS, SMX3000LV,
SMX3000LV2U-BR, SMX3000LVNC,
SMX3000LVNCUS, SMX3000LVUS,
SMX3000RMHV2U, SMX3000RMHV2UNC,
SMX3000RMLVUS, SMX3KRMLVNCUS,
SMX750-NMC, SMX750US, SRT1000RMXLA,
SRT1000RMXLA-NC, SRT1000RMXLI,
SRT1000RMXLI-NC, SRT10KRMXLI,
SRT10RMXLIX806, SRT1500RMXLA,
SRT1500RMXLA-NC, SRT5KRMXLT,
SRT5KRMXLT-IEC, SRT5KRMXLTUS,
SRT5KRMXLW-HW, SRT5KRMXLW-TW,
SRT6KRMXLI, SRT6KRMXLT, SRT6KRMXLT-
IEC, SRT8KRMXLI, SRT8KRMXLT,
SRT8KRMXLT-IEC, SUA3000RMXL3U-BR,
SURT3000XLI-ET, SURT5000XLIX438,
SYA12K16RMICH, SYA16K16RMICH,
SYA8K16RMICH, SYAF16KRMICH

