

APC Easy Metered Rack PDU EPDU1016M - power distribution unit - 3680 VA



Not in stock

SKU	EPDU1016M
Product Description:	APC Easy Metered Rack PDU EPDU1016M - power distribution unit - 3680 VA
Device Type:	Power distribution unit - rack-mountable
Cord Length:	2.5 m
Rack Size:	1U
Weight:	700 g
Input Voltage:	AC 200/208/230 V
Output Voltage:	AC 208/230 V

General

Device Type: Power distribution unit - rack-mountable

Height (Rack Units): 1U

Cord Length: 2.5 m

Colour: Black

Compatibility Information

Power Device

Input Voltage: AC 200/208/230 V

Input Connectors: 1 x power IEC 60320 C20

Power Output Connectors Details: 8 x power IEC 60320 C13

Output Voltage: AC 208/230 V

Max Electric Current: 16 A

Power Capacity: 3680 VA

Networking

Remote Management Interface: Ethernet

Remote Management Protocol: SNMP, Telnet, HTTP

Expansion / Connectivity

Interfaces: 1 x management (Ethernet) - RJ-45 | 1 x sensor

Produktdatablad genereret d. 08-05-2024 02:21.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

Miscellaneous

Included Accessories:	Rack mounting bracket
Cables Included:	Power cable 2.5 m
Features:	LCD display, current meter, firmware upgradable
Compliant Standards:	TUV

Manufacturer Warranty

Service & Support:	Limited warranty - 1 year
--------------------	---------------------------

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	5 - 95%

Compatibility Information

P/N:	ACCS1001, ACDC1015, ACDC1019, AP5017, AP5607, AP7530, AP7532, AP7540, AP7563, AP7852, AP7864, AP7911, AP7951, AP7953, AP9290, AP9553, AP9560, AP9562, AP9564, AR106V, AR112, AR201, AR204A, AR3003SP, AR3006SP, AR3103, AR3103SP, AR3106, AR3106SP, AR3150SP2, AR3300W, AR3350W, AR3357X610, AR3357X617, AR4000MVX432, AR4018A, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR8160ABLK, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, SC450RM1U, SCL400RMJ1U, SCL500RM1UC, SCL500RM1UNC, SCL500RMI1UC, SCL500RMI1UNC, SMC1000, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC1500, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I-2UC, SMC1500IC, SMC2000I, SMC3000I, SMT1000RM2U, SMT2200I, SMT2200IC, SMT2200RM2U, SMT2200RM2UC, SMT2200RMI2U, SMT2200RMI2UC, SMT3000I, SMT3000IC, SMT3000RM2U, SMT3000RM2UC, SMT3000RMI2U, SMT3000RMI2UC, SMTL1000RM2UC, SMTL1000RMI2UC, SMTL750RM2UC, SMTL750RMI2UC, SMX1000, SMX1000I, SMX1500RM2U, SMX1500RMI2U, SMX3000HVNC, SMX3000RMHV2UNC, SMX750I, SRT2200XLI, SRT3000XLW-IEC, SRT5KRMXLI, SU2200R3X167, SUA1000RM1U, SUA1500R2X93, SUA2200R2X106, SUA2200RMI2U, SUA3000I, SUA3000R2X180, SUA3000RMLIBU, SUA5000RMT5U, SUA750RM1U, SUA750RM2U, SUM1500RML2U, SURT10000RMXLT, SURT3000RMXLT-1TF5, SURT3000UXI, SURT3000XLI
------	---

Designed For:

Dimensions & Weight (Shipping)

Shipping Width:	56 cm
Shipping Depth:	8 cm
Shipping Height:	15 cm
Shipping Weight:	1.4 kg

Dimensions & Weight

Dimensions & Weight

Width:	48.2 cm
Depth:	4.44 cm
Height:	4.44 cm
Weight:	700 g

