

APC Metered-by-Outlet Rack PDU 2G - power distribution unit



Not in stock

SKU	AP8481
Product Description:	APC Metered-by-Outlet Rack PDU 2G - power distribution unit
Device Type:	Power distribution unit - rack-mountable
Rack Size:	0U
Weight:	8.21 kg
Input Wiring:	3-phase
Input Voltage:	AC 400 V
Output Voltage:	AC 230 V

General

Device Type:	Power distribution unit - rack-mountable
Height (Rack Units):	0U
Colour:	Black

Power Device

Input Voltage:	AC 400 V
Input Wiring:	3-phase
Frequency Required:	50/60 Hz
Input Connectors:	Power IEC 60309 16A, power IEC 60309 20A
Power Output Connectors Details:	21 x power IEC 60320 C13 3 x power IEC 60320 C19
Output Voltage:	AC 230 V
Max Electric Current:	16 A

Networking

Remote Management Interface:	RS-232
Remote Management Protocol:	SNMP, Telnet, HTTP

Expansion / Connectivity

Interfaces:	1 x management (RS-232)
-------------	-------------------------

Miscellaneous

Compatibility Information

P/N: AP5607, AP7950B, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3100G, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3105, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3150SP, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, NBES0302, NBPDO160A, NBPDO171, NBPDO172, NBPDO180, NBWLO355A, NBWLO356A, SMC1000, SMC1000-2U, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC1500, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RMI2U, SMT1500RM1U, SMT1500RM2U, SMT1500RM1U, SMT2200RM2UC, SMT3000I2U-BR, SMT3000RM2UC, SMT3000RMT2U, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LV, SMX2000LVNC, SMX2000LVNCUS, SMX2000LVUS, SMX2200HV,
--

Miscellaneous

Cables Included: Power cable 1.83 m | Serial cable - external

Rack Mounting Kit:	Included
--------------------	----------

Features: LCD display, LED indicators, overload protection, vertical orientation, firmware upgradable

Compliant Standards:	UL, EN 61000-3-2, ICES-003, VDE, EN 61000-3-3, EN55024, EN55022 Class A, RoHS, FCC Part 15 A, REACH
----------------------	---

Manufacturer Warranty

Service & Support: Limited warranty - 2 years

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	5 - 95%

Dimensions & Weight

Width:	5.6 cm
Depth:	5.1 cm
Height:	182.9 cm
Weight:	8.21 kg

Dimensions & Weight (Shipping)

Shipping Width:	16.3 cm
Shipping Depth:	11.7 cm
Shipping Height:	203.7 cm
Shipping Weight:	10.48 kg

Compatibility Information

SMX2200HVNC, SMX2200R2HVNC, SMX2200RMHV2U, SMX2200RMLV2U, SMX2200RMLVUS, SMX3000HV, SMX3000HV-BR, SMX3000HVNC, SMX3000HVT, SMX3000HVTUS, SMX3000LV, SMX3000LV2U-BR, SMX3000LVNC, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMHV2U, SMX3000RMHV2UNC, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750C, SMX750CNC, SMX750-NMC, SMX750US, SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT1000RMXLI-NC, SRT10KRMXLI, SRT10RMXLIX806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT5KRMXLT, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-HW, SRT5KRMXLW-TW, SRT6KRMXLI, SRT6KRMXLT, SRT6KRMXLT-IEC, SRT8KRMXLI, SRT8KRMXLT, SRT8KRMXLT-IEC, SUA3000RMXL3U-BR, SURT3000XLI-ET, SURT5000XLIX438, SYA12K16RMICH, SYA16K16RMICH, SYA8K16RMICH, SYAF16KRMICH