

APC Metered Rack PDU AP7811B - power distribution unit



Not in stock

SKU	AP7811B
Product Description:	APC Metered Rack PDU AP7811B - power distribution unit
Device Type:	Power distribution unit - rack-mountable
Rack Size:	2U
Weight:	3.36 kg
Input Voltage:	AC 200/208/230 V
Output Voltage:	AC 208 V
Input Connectors:	1 x power NEMA L6-30

General

Device Type:	Power distribution unit - rack-mountable
Height (Rack Units):	2U

Power Device

Input Voltage:	AC 200/208/230 V
Frequency Required:	50/60 Hz
Input Connectors:	1 x power NEMA L6-30
Power Output Connectors Details:	12 x power IEC 60320 C13 4 x power IEC 60320 C19
Output Voltage:	AC 208 V
Max Electric Current:	30 A
Circuit Protection:	Circuit breaker

Networking

Remote Management Interface:	Ethernet
------------------------------	----------

Expansion / Connectivity

Interfaces:	1 x management (Ethernet) - RJ-45
-------------	-----------------------------------

Miscellaneous

Cables Included:	Power cable - integrated - 3.66 m
------------------	-----------------------------------

Compatibility Information

P/N:	AP4431, AP7950B, AR106, AR106SH4, AR106SH6, AR109SH4, AR109SH6, AR112, AR112SH4, AR112SH6, AR2487G, AR3003, AR3003SP, AR3006, AR3006SP, AR3100W, AR3103, AR3103SP, AR3105SP, AR3105W, AR3106, AR3106SP, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR3357X674, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, AR8213, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBPDO160A, NBWLO355A, NBWLO356A, SCL400RM1U, SCL500RM1UC, SCL500RM1UNC, SCL500RM1IUC, SCL500RM1IUNC, SMC1000-BR, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RM12U, SMT2200RM2UC, SMT3000I2U-BR, SMT3000RM2UC, SMTL1000RM2UC, SMTL1000RM12UC, SMTL750RM2UC, SMTL750RM12UC, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LVNCUS, SMX2000LVUS, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMLVUS, SMX3000HV-BR, SMX3000HVTUS, SMX3000LV2U-BR, SMX3000LVNCUS, SMX3000LVUS,
------	--

Designed For:

Miscellaneous

Rack Mounting Kit:	Included
--------------------	----------

Features: Current meter, overload protection

Compliant Standards:	FCC Class A certified, CSA, UL, cUL, ICES-003, UL 60950, FCC Part 15, RoHS, PSE Mark, REACH SvHC
----------------------	--

Manufacturer Warranty

Service & Support: Limited warranty - 2 years

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	5 - 95%

Dimensions & Weight

Width:	44.4 cm
Depth:	11.2 cm
Height:	8.8 cm
Weight:	3.36 kg

Dimensions & Weight (Shipping)

Shipping Width:	50.8 cm
Shipping Depth:	36.8 cm
Shipping Height:	14 cm
Shipping Weight:	5.42 kg

Compatibility Information

SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750C, SMX750CNC, SMX750US, SRT1000RMLA, SRT1000RMLA-NC, SRT1000RMLI, SRT10KRMLT, SRT10KRMLT-10KTF, SRT10KRMLT30, SRT10KRMLT-5KTF2, SRT10KXLT, SRT10KXLT30, SRT10KXLT-5KTF2, SRT10KXLTUS, SRT10KXLTW, SRT10RMLIX806, SRT1500RMLA, SRT1500RMLA-NC, SRT3000RMLT, SRT3000RMLT-5KTF, SRT3000RMLT-NC, SRT3000XLT, SRT3000XLT-5KTF, SRT3000XLTW, SRT5KRMLT, SRT5KRMLT-5KTF, SRT5KRMLT-IEC, SRT5KRMLTUS, SRT5KRMLW-HW, SRT5KRMLW-TW, SRT5KXLJ, SRT5KXLT, SRT5KXLT-5KTF, SRT5KXLTUS, SRT6KRMLT, SRT6KRMLT-5KTF, SRT6KRMLT-IEC, SRT6KXLT, SRT6KXLT-5KTF, SRT6KXLTUS, SRT6KXLTW, SRT8KRMLT, SRT8KRMLT30, SRT8KRMLT-5KTF, SRT8KRMLT-IEC, SRT8KXLJ, SRT8KXLT, SRT8KXLT30, SRT8KXLT-5KTF, SRT8KXLTUS, SRT5000RMLIX438, SYAF16KRMLCH