

APC Metered Rack PDU AP7822B - power distribution unit



SKU	AP7822B
Product Description:	APC Metered Rack PDU AP7822B - power distribution unit
Device Type:	Power distribution unit - rack-mountable
Cord Length:	3.66 m
Rack Size:	2U
Weight:	3.36 kg
Input Voltage:	AC 200/208/230 V
Output Voltage:	AC 230 V

In Stock(2)

General

Device Type:	Power distribution unit - rack-mountable
Height (Rack Units):	2U
Cord Length:	3.66 m

Power Device

Input Voltage:	AC 200/208/230 V
Frequency Required:	50/60 Hz
Input Connectors:	1 x power IEC 60309 32A
Power Output Connectors Details:	12 x power IEC 60320 C13 ; 4 x power IEC 60320 C19
Output Voltage:	AC 230 V
Max Electric Current:	32 A
Circuit Protection:	Circuit breaker

Miscellaneous

Cables Included:	Power cable 3.66 m
Rack Mounting Kit:	Included
Features:	Horizontal orientation, LED display, current meter, overload protection
Compliant Standards:	VCCI, C-Tick, GOST, ICES-003, VDE, MIC, IRAM, RoHS, FCC Part 15 A, REACH

Compatibility Information

P/N: ACDC2513, AP7950B, AR106, AR112, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3100G, AR3100TAA, AR3100W, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3180G, AR3300G, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR8213, DLT3000RMI2U, NBES0302, NBPDO160A, NBPDO180, NBWL0355A, NBWL0356A, SCL400RMJ1U, SCL500RM1UC, SCL500RM1UNC, SCL500RM1UC, SCL500RM1UNC, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RMI2U, SMT1500RM1U, SMT1500RM2U, SMT1500RM1IU, SMT2200RM2UC, SMT2200RM12UC, SMT3000I2U-BR, SMT3000RM2UC, SMTL1000RM2UC, SMTL1000RMI2UC, SMTL750RM2UC, SMTL750RMI2UC, SMX1000US, SMX1500RMNCUS, SMX1500RMUS, SMX2000LV, SMX2000LVNC,

Designed For:

Manufacturer Warranty

Service & Support: Limited warranty - 2 years

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	5 - 95%

Dimensions & Weight

Width:	44.4 cm
Depth:	11.2 cm
Height:	8.8 cm
Weight:	3.36 kg

Dimensions & Weight (Shipping)

Shipping Width:	50.8 cm
Shipping Depth:	36.8 cm
Shipping Height:	14 cm
Shipping Weight:	5.42 kg

Compatibility Information

SMX2000LVNCUS, SMX2000LVUS,
SMX2200HV, SMX2200HVNC,
SMX2200R2HVNC, SMX2200RMHV2U,
SMX2200RMLVUS, SMX3000HV,
SMX3000HV-BR, SMX3000HVNC,
SMX3000HVT, SMX3000HVTUS,
SMX3000LV, SMX3000LV2U-BR,
SMX3000LVNC, SMX3000LVNCUS,
SMX3000LVUS, SMX3000RMLVUS,
SMX3KRMLVNCUS, SMX750-NMC,
SMX750US, SRT1000RMXLA,
SRT1000RMXLA-NC, SRT1000RMXLI,
SRT1000RMXLI-NC, SRT10KRMXLI,
SRT10RMXLIX806, SRT1500RMXLA,
SRT1500RMXLA-NC, SRT1500XLI,
SRT2200RMXLI-NC, SRT2200XLI-KR,
SRT3000RMXLI-NC, SRT5KRMXLIM,
SRT5KRMXLT, SRT5KRMXLT-IEC,
SRT5KRMXLTUS, SRT5KRMXLW-HW,
SRT5KRMXLW-TW, SRT6KRMXLI,
SRT6KRMXLIM, SRT6KRMXLT, SRT6KRMXLT-IEC,
SRT8KRMXLI, SRT8KRMXLT,
SRT8KRMXLT-IEC, SRT3000XLI-ET,
SURT5000XLIX438, SYAF16KRMICH

