

APC Metered Rack PDU AP7850B - power distribution unit



Not in stock

SKU	AP7850B
Product Description:	APC Metered Rack PDU AP7850B - power distribution unit
Device Type:	Power distribution unit - rack-mountable
Cord Length:	3.05 m
Rack Size:	0U
Weight:	3.06 kg
Input Voltage:	AC 230 V
Output Voltage:	AC 230 V

General

Device Type:	Power distribution unit - rack-mountable
Height (Rack Units):	0U
Cord Length:	3.05 m

Power Device

Input Voltage:	AC 230 V
Input Voltage Margin:	± 10%
Input Connectors:	1 x power IEC 60320 C14
Power Output Connectors Details:	16 x power IEC 60320 C13
Output Voltage:	AC 230 V

Networking

Remote Management Protocol:	SNMP, Telnet, SSH
-----------------------------	-------------------

Miscellaneous

Cables Included:	Power cable - integrated - 3.05 m
Rack Mounting Kit:	Included
Features:	Horizontal orientation, LED display, current meter
Compliant Standards:	EN55022, VDE, EN55024, EAC, AS/NZS CISPR 22

Compatibility Information

P/N: AP7950B, AR2200, AR2280, AR2487G, AR3100TAA, AR3100W, AR3105SP, AR3105W, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR3357X674, AR4038IX432, NBPD0160A, NBWL0355A, NBWL0356A, SCL500RMI1UC, SCL500RMI1UNC, SMC1000-BR, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I, SMC2000I-2U, SMC3000I, SMC3000RMI2U, SMT1000I-6W, SMT1000I-AR, SMT1000IC, SMT1000R2I-AR, SMT1000RMI2UC, SMT1500I-AR, SMT1500IC, SMT1500R2I-6W, SMT1500R2I-AR, SMT1500RMI2UC, SMT1500RMI2UNC, SMT2200I-AR, SMT2200IC, SMT2200R2I-AR, SMT2200RMI2UC, SMT2200RMI2UNC, SMT2200RMI2UNC, SMT3000I2U-BR, SMT3000I-AR, SMT3000IC, SMT3000R2I-6W, SMT3000R2I-AR, SMT3000RMI2UC, SMT3000RMI2UNC, SMT750RMI2UC, SMT750RMI2UNC, SMTL750RMI2UC, SMX1000C, SMX1000US, SMX1500RMI2UC, SMX1500RMI2UNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LVNCUS, SMX2000LVUS, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMLVUS, SMX3000HV-BR, SMX3000HVTUS, SMX3000LV2U-BR, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750C, SMX750CNC, SMX750INC, SMX750US, SRC2000XLI-CC, SRC3KUXI,
--

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	5 - 95% (non-condensing)

Dimensions & Weight

Width:	5.59 cm
Depth:	4.45 cm
Height:	124.46 cm
Weight:	3.06 kg

Dimensions & Weight (Shipping)

Shipping Width:	15.24 cm
Shipping Depth:	12.7 cm
Shipping Height:	213.36 cm
Shipping Weight:	3.97 kg

Compatibility Information

SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT1000RMXLI-NC, SRT10KRMXLI, SRT10KRMXLT-IEC, SRT10KXLT-IEC, SRT10RMXLIX806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT1500RMXLI, SRT1500XLI, SRT2200RMXLI, SRT2200RMXLI-NC, SRT2200XLI, SRT2200XLI-KR, SRT3000RMXLI, SRT3000RMXLI-NC, SRT3000RMXLW-IEC, SRT3000XLI, SRT3000XLW-IEC, SRT5KRMXLI-6W, SRT5KRMXLIM, SRT5KRMXLT, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-HW, SRT5KRMXLW-TW, SRT6KRMXLI-6W, SRT6KRMXLIM, SRT6KRMXLT, SRT6KRMXLT-IEC, SRT6KXLT-IEC, SRT8KRMXLT, SRT8KRMXLT-IEC, SRT8KXLT-IEC, SUA1000ICH-45, SUA1500ICH-45, SUA1500I-IN, SUA2200ICH-45, SUA3000ICH-45, SUA3000I-IN, SUA750ICH-45, SURT1000RMXLI-NC, SURT1000XLI-NC, SURT5000XLIX438, SYAF16KRMICH

