

APC Metered Rack PDU - power distribution unit - 10 kW



Not in stock

SKU	AP8868
Product Description:	APC Metered Rack PDU - power distribution unit - 10 kW
Device Type:	Power distribution unit - rack-mountable
Rack Size:	0U
Weight:	8.5 kg
Localisation:	Canada, United States
Input Wiring:	3-phase
Input Voltage:	AC 208 V

General

Device Type:	Power distribution unit - rack-mountable
Height (Rack Units):	0U
Colour:	Black
Localisation:	Canada, United States

Power Device

Input Voltage:	AC 208 V
Input Wiring:	3-phase
Frequency Required:	50/60 Hz
Input Connectors:	1
Power Output Connectors Details:	36 x power IEC 60320 C13 6 x power IEC 60320 C19
Output Voltage:	AC 208 V
Max Electric Current:	35 A
Power Capacity:	10 kW
Circuit Protection:	Circuit breaker

Networking

Remote Management Interface:	Ethernet 10/100, RS-232
Remote Management Protocol:	SNMP, Telnet, HTTP

Expansion / Connectivity

Compatibility Information

P/N: AP7950B, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3100G, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3105, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140G, AR3140W, AR3150SP, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, NBES0302, NBPDO160A, NBPDO171, NBPDO172, NBPDO180, NBWLO355A, NBWLO356A, SMC1000, SMC1000-2U, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC1500, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RM2U, SMT1500RM1U, SMT1500RM2U, SMT1500RM11U, SMT2200RM2UC, SMT3000I2U-BR, SMT3000RM2UC, SMT3000RMT2U, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LV, SMX2000LVNC, SMX2000LVNCUS,

Designed For:

Produktdatablad genereret d. 16-09-2024 22:10.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

Expansion / Connectivity

Interfaces: 1 x management (RS-232) | 1 x management (Ethernet) - RJ-45

Miscellaneous

Cables Included: Power cable - integrated - 1.8 m

Rack Mounting Kit: Included

Features: Current meter, overload protection

Compliant Standards: FCC Class A certified, UL, cUL, ICES-003, VCCI Class A ITE, FCC Part 15, RoHS Exemption 7b, UL 60950-1, CSA C22.2 No. 60950-1-03

Manufacturer Warranty

Service & Support: Limited warranty - 2 years

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 50 °C

Humidity Range Operating: 5 - 95%

Dimensions & Weight

Width: 5.6 cm

Depth: 5.1 cm

Height: 183 cm

Weight: 8.5 kg

Dimensions & Weight (Shipping)

Shipping Width: 17 cm

Shipping Depth: 11.2 cm

Shipping Height: 205 cm

Shipping Weight: 11.4 kg

Compatibility Information

SMX2000LVUS, SMX2200HV,
SMX2200HVNC, SMX2200R2HVNC,
SMX2200RMHV2U, SMX2200RMLVUS,
SMX3000HV, SMX3000HV-BR,
SMX3000HVNC, SMX3000HVT,
SMX3000HVTUS, SMX3000LV,
SMX3000LV2U-BR, SMX3000LVNC,
SMX3000LVNCUS, SMX3000LVUS,
SMX3000RMHV2U, SMX3000RMHV2UNC,
SMX3000RMLVUS, SMX3KRMLVNCUS,
SMX750C, SMX750CNC, SMX750-NMC,
SMX750US, SRT1000RMXLA,
SRT1000RMXLA-NC, SRT1000RMXLI,
SRT10KRMXLI, SRT10RMXLIX806,
SRT1500RMXLA, SRT1500RMXLA-NC,
SRT5KRMXLT, SRT5KRMXLT-IEC,
SRT5KRMXLTUS, SRT5KRMXLW-HW,
SRT5KRMXLW-TW, SRT6KRMXLI,
SRT6KRMXLT, SRT6KRMXLT-IEC,
SRT8KRMXLI, SRT8KRMXLT, SRT8KRMXLT-IEC,
SURT3000XLI-ET, SURT5000XLIX438,
SYA12K16RMICH, SYA16K16RMICH,
SYA8K16RMICH, SYAF16KRMICH,
SYAF8KRMTX424