

APC Metered Rack PDU - power distribution unit - 17.3 kW



Not in stock

SKU	AP8866
Product Description:	APC Metered Rack PDU - power distribution unit - 17.3 kW
Device Type:	Power distribution unit - rack-mountable
Rack Size:	0U
Weight:	9.6 kg
Localisation:	Canada, United States
Input Wiring:	3-phase
Input Voltage:	AC 208 V

General

Device Type:	Power distribution unit - rack-mountable
Height (Rack Units):	0U
Colour:	Black
Localisation:	Canada, United States

Power Device

Input Voltage:	AC 208 V
Input Wiring:	3-phase
Frequency Required:	50/60 Hz
Input Connectors:	1 x power IEC 60309
Power Output Connectors Details:	6 x power IEC 60320 C13 12 x power IEC 60320 C19
Output Voltage:	AC 208 V
Max Electric Current:	60 A
Power Capacity:	17.3 kW
Circuit Protection:	Circuit breaker

Networking

Remote Management Interface:	Ethernet 10/100, RS-232
Remote Management Protocol:	SNMP, Telnet, HTTP

Expansion / Connectivity

Compatibility Information

P/N:	AP7950B, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3100G, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3107X609, AR3140G, AR3140W, AR3150SP, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155SP, AR3155W, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3307X609, AR3307X617, AR3340G, AR3340W, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355SP, AR3355W, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, AR4018A, AR4018IA, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4024IA, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBES0302, NBPDO160A, NBPDO180, NBWL0355A, NBWL0356A, SMC1000, SMC1000-2U, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC1500, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RMI2U, SMT1500RM1U, SMT1500RM2U, SMT1500RMI1U, SMT2200RM2UC, SMT3000I2U-BR, SMT3000RM2UC, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS,
------	---

Expansion / Connectivity

Interfaces:	1 x management (RS-232) 1 x management (Ethernet) - RJ-45
-------------	---

Miscellaneous

Cables Included:	Power cable - integrated - 1.8 m
------------------	----------------------------------

Rack Mounting Kit:	Included
--------------------	----------

Features:	Current meter, overload protection
-----------	------------------------------------

Compliant Standards:	FCC Class A certified, UL, cUL, ICES-003, VCCI Class A ITE, FCC Part 15, RoHS Exemption 7b, UL 60950-1, CSA C22.2 No. 60950-1-03
----------------------	--

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	5 - 95%

Dimensions & Weight

Width:	5.6 cm
Depth:	5.1 cm
Height:	183 cm
Weight:	9.6 kg

Dimensions & Weight (Shipping)

Shipping Width:	22.1 cm
Shipping Depth:	11.2 cm
Shipping Height:	215 cm
Shipping Weight:	13.6 kg

Compatibility Information

SMX1500RMUS, SMX2000LV, SMX2000LVNC, SMX2000LVNCUS, SMX2000LVUS, SMX2200HV, SMX2200HVN, SMX2200R2HVN, SMX2200RMHV2U, SMX2200RMLVUS, SMX3000HV, SMX3000HV-BR, SMX3000HVN, SMX3000HVT, SMX3000HVTUS, SMX3000LV, SMX3000LV2U-BR, SMX3000LVNC, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750C, SMX750CNC, SMX750-NMC, SMX750US, SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT10KRMXLI, SRT10RMXLI806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT5KRMXLT, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-HW, SRT5KRMXLW-TW, SRT6KRMXLI, SRT6KRMXLT, SRT6KRMXLT-IEC, SRT8KRMXLI, SRT8KRMXLT, SRT8KRMXLT-IEC, SURT3000XLI-ET, SURT5000XLIX438, SYA12K16RMICH, SYAF16KRMICH, SYAF8KRMTX424