

# APC Metered Rack PDU - power distribution unit



|                      |                                                |
|----------------------|------------------------------------------------|
| SKU                  | AP8886                                         |
| Product Description: | APC Metered Rack PDU - power distribution unit |
| Device Type:         | Power distribution unit - rack-mountable       |
| Rack Size:           | 0U                                             |
| Weight:              | 8.72 kg                                        |
| Input Wiring:        | 3-phase                                        |
| Input Voltage:       | AC 400 V                                       |
| Output Voltage:      | 230 V                                          |

## General

|                      |                                          |
|----------------------|------------------------------------------|
| Device Type:         | Power distribution unit - rack-mountable |
| Height (Rack Units): | 0U                                       |
| Colour:              | Black                                    |

## Power Device

|                                  |                                                     |
|----------------------------------|-----------------------------------------------------|
| Input Voltage:                   | AC 400 V                                            |
| Input Wiring:                    | 3-phase                                             |
| Frequency Required:              | 50/60 Hz                                            |
| Input Connectors:                | 1 x power IEC 60309 32A                             |
| Power Output Connectors Details: | 30 x power IEC 60320 C13   12 x power IEC 60320 C19 |
| Output Voltage:                  | 230 V                                               |
| Max Electric Current:            | 32 A                                                |
| Circuit Protection:              | Circuit breaker                                     |

## Networking

|                              |                         |
|------------------------------|-------------------------|
| Remote Management Interface: | Ethernet, RS-232, USB   |
| Remote Management Protocol:  | SNMP, Telnet, HTTP, SSH |

## Expansion / Connectivity

|             |                                                          |
|-------------|----------------------------------------------------------|
| Interfaces: | 1 x management (Ethernet) - RJ-45   1 x serial   1 x USB |
|-------------|----------------------------------------------------------|

## Compatibility Information

|      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| P/N: | AP5607, AP7950B, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3100G, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3103SP, AR3105, AR3105SP, AR3105W, AR3106SP, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140G, AR3140W, AR3150SP, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3180G, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, NBES0302, NBPDO160A, NBPDO171, NBPDO172, NBPDO180, NBWL0355A, NBWL0356A, SMC1000, SMC1000-2U, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC1500, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RM2U, SMT1500RM1U, SMT1500RM2U, SMT1500RM1U, SMT2200RM2UC, SMT3000I2U-BR, SMT3000RM2UC, SMT3000RMT2U, SMX1000US, SMX1500RMNCUS, SMX1500RMUS, SMX2000LV, SMX2000LVNC, SMX2000LVNCUS, |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Miscellaneous

Cables Included: Power cable 1.8 m | Serial cable - external

Rack Mounting Kit: Included

Features: LCD display, current meter, over current protection, overload protection

Compliant Standards: EN 61000-3-2, ICES-003, VDE, VCCI Class A ITE, EN 61000-3-3, EN55024, EN55022 Class A, RoHS, FCC Part 15 A, REACH

Manufacturer Warranty

Service & Support: Limited warranty - 2 years

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 50 °C

Humidity Range Operating: 5 - 95%

Dimensions & Weight

Width: 5.6 cm

Depth: 5.1 cm

Height: 182.9 cm

Weight: 8.72 kg

Dimensions & Weight (Shipping)

Shipping Width: 17 cm

Shipping Depth: 12 cm

Shipping Height: 205 cm

Shipping Weight: 11.6 kg

Compatibility Information

SMX2000LVUS, SMX2200HV, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMHV2U, SMX2200RMLVUS, SMX3000HV, SMX3000HV-BR, SMX3000HVNC, SMX3000HVT, SMX3000HVTUS, SMX3000LV, SMX3000LV2U-BR, SMX3000LVNC, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMHV2U, SMX3000RMHV2UNC, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750-NMC, SMX750US, SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT1000RMXLI-NC, SRT10KRMXLI, SRT10RMXLIX806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT5KRMXLT, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-HW, SRT5KRMXLW-TW, SRT6KRMXLI, SRT6KRMXLT, SRT6KRMXLT-IEC, SRT8KRMXLI, SRT8KRMXLT, SRT8KRMXLT-IEC, SUA3000RMXL3U-BR, SURT3000XLI-ET, SURT5000XLIX438, SYA12K16RMICH, SYA16K16RMICH, SYA8K16RMICH, SYAF16KRMICH