

APC Service Bypass Panel - power distribution unit - 1500 VA



Not in stock

SKU	SBP1500RM
Product Description:	APC Service Bypass Panel - power distribution unit - 1500 VA
Device Type:	Power distribution unit - rack-mountable
Weight:	3 kg
Input Voltage:	AC 120 V
Output Voltage:	AC 120 V
Power Capacity:	1500 VA
Input Connectors:	Power NEMA 5-15

General

Device Type:	Power distribution unit - rack-mountable
Colour:	Black

Power Device

Input Voltage:	AC 120 V
Input Voltage Range:	AC 100 - 125 V
Frequency Required:	50/60 Hz
Input Connectors:	Power NEMA 5-15
Power Output Connectors Details:	8 x power NEMA 5-15
Output Voltage:	AC 120 V
Max Electric Current:	15 A
Power Capacity:	1500 VA

Miscellaneous

Cables Included:	Power cable 2.4 m
Rack Mounting Kit:	Included
Features:	Built-in bypass switch, overload protection
Compliant Standards:	TUV, RoHS Exemption 7b, REACH

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Compatibility Information

P/N: AR3180G, AR3357X674, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBES0302, NBPDO160A, NBPDO171, NBPDO172, NBPDO180, NBWL0355A, NBWL0356A, SCL400RMJ1U, SCL500RM1UC, SCL500RM1UNC, SMC1000, SMC1000-2U, SMC1000-2UC, SMC1000-2UTW, SMC1000C, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC1000TW, SMC1500, SMC1500-2U, SMC15002U-BR, SMC1500-2UC, SMC1500-2UTW, SMC1500-BR, SMC1500C, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500IC, SMC1500TW, SMC2000I-2U, SMC3000RMI2U, SMT1000C, SMT1000J, SMT1000J3W, SMT1000J5W, SMT1000J053, SMT1000J055, SMT1000J056, SMT1000RM2UC, SMT1000US, SMT1500C, SMT1500J, SMT1500NC, SMT1500R2-NMC, SMT1500R2X122, SMT1500R2X180, SMT1500RM1U, SMT1500RM2U, SMT1500RM2UC, SMT1500RM2UNC, SMT1500RM2UTW, SMT1500RM11U, SMT1500RMJ2U, SMT1500RMUS, SMT1500TW, SMT1500US, SMT1500X413, SMT1500X448, SMT2200RM2UC, SMT3000RM2U, SMT3000RM2UC, SMT3000RMT2U, SMT500J, SMT500J5W, SMT500J055, SMT750C, SMT750J, SMT750J3W, SMT750J5W, SMT750J053, SMT750J055, SMT750J056, SMT750R2-NMC, SMT750R2X122, SMT750RM2U, SMT750RM2UC, SMT750RM2UNC, SMT750TW, SMT750US, SMTL1000RM2UC, SMTL750RM2UC, SMX1000C, SMX1000US, SMX1500RM2UCNC, SMX1500RMNCUS, SMT1500RMUS, SMX2000LV,

Designed For:

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	0 - 95%

Dimensions & Weight

Width:	43.2 cm
Depth:	7.6 cm
Height:	8.9 cm
Weight:	3 kg

Dimensions & Weight (Shipping)

Shipping Width:	46.3 cm
Shipping Depth:	29.5 cm
Shipping Height:	15.1 cm
Shipping Weight:	3.8 kg

Compatibility Information

SMX2000LVNC, SMX2000LVNCUS, SMX2000LVUS, SMX2000RMLV2U, SMX2200HV, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMHV2U, SMX2200RMLV2U, SMX2200RMLVUS, SMX3000HV, SMX3000HV-BR, SMX3000HVNC, SMX3000HVT, SMX3000HVTUS, SMX3000LV, SMX3000LV2U-BR, SMX3000LVNC, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMHV2U, SMX3000RMHV2UNC, SMX3000RMLV2U, SMX3000RMLV2UNC, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750C, SMX750NC, SMX750-NMC, SMX750US, SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT10KRMXLI, SRT10RMXLIX806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT5KRMXLT, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-HW, SRT5KRMXLW-TW, SRT6KRMXLI, SRT6KRMXLT, SRT6KRMXLT-IEC, SRT8KRMXLI, SRT8KRMXLT, SRT8KRMXLT-IEC, SUA1000RM2UTW, SURT3000XLI-ET, SYA12K16RMICH, SYA16K16RMICH, SYA8K16RMICH, SYAF16KRMICH

