

APC Service Bypass Panel - power distribution unit - 3000 VA



Not in stock

SKU	SBP3000RMHW
Product Description:	APC Service Bypass Panel - power distribution unit - 3000 VA
Device Type:	Power distribution unit - rack-mountable
Rack Size:	2U
Weight:	2.3 kg
Input Voltage:	AC 230 V
Output Voltage:	AC 230 V
Power Capacity:	3000 VA

General

Device Type:	Power distribution unit - rack-mountable
Height (Rack Units):	2U
Colour:	Black

Power Device

Input Voltage:	AC 230 V
Input Voltage Range:	AC 220 - 240 V
Frequency Required:	50/60 Hz
Input Connectors:	2 x power IEC 60320 C20, hardwire
Power Output Connectors Details:	1 x hardwire 3-wire (HN + G) ; 1 x power IEC 60320 C19
Output Voltage:	AC 230 V
Max Electric Current:	16 A
Power Capacity:	3000 VA

Miscellaneous

Rack Mounting Kit:	Included
Features:	Built-in bypass switch, overload protection
Compliant Standards:	VDE, RoHS, REACH

Compatibility Information

	P/N: DLT3000RM12U, SMC2000I, SMC2000I-2U, SMC3000I, SMC3000RM12U, SMT2200I, SMT2200I-AR, SMT2200IC, SMT2200R2I-AR, SMT2200RM12U, SMT2200RM12UC, SMT2200RM12UNC, SMT3000I, SMT3000I-AR, SMT3000IC, SMT3000R2I-6W, SMT3000R2I-AR, SMT3000RM12U, SMT3000RM12UC, SMT3000RM12UNC, SMX2200HV, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMHV2U, SMX3000HV, SMX3000HVNC, SMX3000HVT, SMX3000HVTUS, SMX3000RMHV2U, SMX3000RMHV2UNC, SRT1500XLI, SRT2200RMXLI, SRT2200RMXLI-NC, SRT2200XLI, SRT2200XLI-KR, SRT3000RMXLI, SRT3000RMXLI-NC, SRT3000RMXLW-IEC, SRT3000XLI, SRT3000XLW-IEC, SUA2200I, SUA2200ICH-45, SUA2200RMXLI3U, SUA2200UXICH, SUA3000I, SUA3000ICH, SUA3000ICH-45, SUA3000I-IN, SUA3000R2ICH, SUA3000RM12U, SUA3000RMXLI3U, SUA3000UXICH, SUA3000XLI, SURT3000XLI, SURTD3000RMXLI, SURTD3000UXI, SURTD3000XLI, SURTD3000XLI-CC
Designed For:	

Dimensions & Weight (Shipping)

Shipping Width:	46.3 cm
Shipping Depth:	29.5 cm
Shipping Height:	15.1 cm
Shipping Weight:	3.5 kg

Manufacturer Warranty

Service & Support: Limited warranty - 2 years

Dimensions & Weight

Width:	43.2 cm
Depth:	7.6 cm
Height:	8.9 cm
Weight:	2.3 kg

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	0 - 95%

