

APC Smart-UPS 1500VA LCD RM - UPS - 1000 Watt - 1500 VA - with APC SmartConnect



In Stock(10)

SKU	SMT1500RM12UC
Product Description:	APC Smart-UPS 1500VA LCD RM - UPS - 1000 Watt - 1500 VA - with APC SmartConnect
Device Type:	UPS - rack-mountable
Rack Size:	2U
Weight:	26.1 kg
Input Voltage:	AC 220/230/240 V
Output Voltage:	AC 220/230/240 V
Power Capacity:	1000 Watt / 1500 VA

General

Device Type:	UPS - rack-mountable
Height (Rack Units):	2U
Colour:	Black
Bundled with:	APC SmartConnect

Compatibility Information

Power Device

UPS Technology:	Line interactive
Input Voltage:	AC 220/230/240 V
Input Voltage Range:	AC 160 - 286 V
Input Voltage Range (Adjustable):	AC 151 - 302 V
Frequency Provided:	57 - 63 Hz
Frequency Required:	50/60 Hz
Input Connectors:	Power IEC 60320 C14
Power Output Connectors Details:	4 x power IEC 60320 C13
Output Voltage:	AC 220/230/240 V 57 - 63 Hz
Power Capacity:	1000 Watt / 1500 VA
Output Waveform:	Sinewave
Surge Suppression:	Yes

Surge Energy Rating:

459 Joules

Produktet er tilgængeligt d. 02-05-2024 20:50.
Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

Power Device

Circuit Protection:	Circuit breaker
---------------------	-----------------

Battery

Technology:	Lead Acid
Run Time (Up To):	7.2 min at full load
Recharge Time:	3 hours
Transfer Time:	6 ms
Features:	Maintenance free, sealed, leak-proof

Networking

Remote Management Interface:	RS-232, USB
Remote Management Protocol:	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SSH-2

Expansion / Connectivity

Interfaces:	1 x management (USB) - 4 pin USB Type B 1 x management (RS-232) - RJ-45
Expansion Slots:	1 SmartSlot

Miscellaneous

Cables Included:	Serial cable USB cable
Rack Mounting Kit:	Included
Features:	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators
Compliant Standards:	CSA, UL 1778, VDE, IEC 62040-2, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1

Software / System Requirements

Software Included:	APC PowerChute Business Edition
--------------------	---------------------------------

Sustainability Information

Compatibility Information

P/N:	ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF400, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR106V, AR106VI, AR1125H6, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3003SP, AR3006, AR3006SP, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3103, AR3103SP, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3106, AR3106SP, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X432, AR7007, AR7050, AR7057, NBWL0356A
------	---

Designed For:

Sustainability Information

ENERGY STAR: Yes

Manufacturer Warranty

Service & Support: Limited warranty - 3 years | Limited warranty - batteries - 2 years

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	0 - 95%
Sound Emission:	46 dBA

Dimensions & Weight

Width:	43.2 cm
Depth:	47.7 cm
Height:	8.6 cm
Weight:	26.1 kg

Dimensions & Weight (Shipping)

Shipping Width:	59.4 cm
Shipping Depth:	60.3 cm
Shipping Height:	25.1 cm
Shipping Weight:	31.91 kg

