

APC Smart-UPS SMT3000RMI2UC - UPS - 2700 Watt - 3000 VA - with APC SmartConnect



In Stock(5)

SKU	SMT3000RMI2UC
Product Description:	APC Smart-UPS SMT3000RMI2UC - UPS - 2700 Watt - 3000 VA - with APC SmartConnect
Device Type:	UPS - rack-mountable
Rack Size:	2U
Weight:	44.28 kg
Input Voltage:	AC 220/230/240 V
Output Voltage:	AC 220/230/240 V ± 5%
Power Capacity:	2700 Watt / 3000 VA

General

Device Type:	UPS - rack-mountable
Height (Rack Units):	2U
Colour:	Black
Bundled with:	APC SmartConnect

Compatibility Information

Power Device

UPS Technology:	Line interactive
Input Voltage:	AC 220/230/240 V
Input Voltage Range:	AC 160 - 286 V
Input Voltage Range (Adjustable):	AC 151 - 302 V
Frequency Provided:	50/60 Hz ± 3Hz
Frequency Required:	50/60 Hz ± 3Hz
Input Connectors:	1 x power IEC 60320 C20, power BS 1363, power CEE 7/7
Power Output Connectors Details:	8 x power IEC 60320 C13 3 x IEC jumper 1 x power IEC 60320 C19
Output Voltage:	AC 220/230/240 V ± 5% - 50/60 Hz

Power Device

Power Capacity:	2700 Watt / 3000 VA
Output Waveform:	Sinewave
Surge Suppression:	Yes
Surge Energy Rating:	365 Joules
Circuit Protection:	Circuit breaker

Battery

Quantity:	1
Technology:	Lead Acid
Run Time (Up To):	3.2 min at full load 11.5 min at half load
Recharge Time:	3 hours
Transfer Time:	6 ms
Features:	Maintenance free, sealed, leak-proof

Networking

Remote Management Interface:	RS-232, USB
------------------------------	-------------

Expansion / Connectivity

Interfaces:	1 x management (RS-232) - RJ-45 1 x management (USB)
Expansion Slots:	1 (total) / 1 (free) x SmartSlot

Miscellaneous

Cables Included:	Serial cable - external USB cable - external
Rack Mounting Kit:	Included
Features:	Audible alarm, emergency power off, LCD display, Automatic Voltage Regulation (AVR), cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre
Compliant Standards:	CSA, UL 1449, UL 1778, FCC Part 15 A

Compatibility Information

P/N:	ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF002, ACF101BLK, ACF102BLK, ACF400, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3003, AR3003SP, AR3006, AR3006SP, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3103, AR3103SP, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3106, AR3106SP, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X432, AR7007, AR7050, AR7057, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBWL0356A
------	---

Designed For:

Software / System Requirements

Software Included: APC PowerChute Business Edition

Manufacturer Warranty

Service & Support: Limited warranty - replace or repair - 3 years † Limited warranty - batteries - 2 years

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	0 - 95%
Sound Emission:	55 dBA

Dimensions & Weight

Width:	48 cm
Depth:	68.3 cm
Height:	8.6 cm
Weight:	44.28 kg

Dimensions & Weight (Shipping)

Shipping Width:	60 cm
Shipping Depth:	98 cm
Shipping Height:	25.4 cm
Shipping Weight:	51.7 kg

