

# APC Smart-UPS SMT750IC - UPS - 500 Watt - 750 VA - with APC SmartConnect



In Stock(2)

|                      |                                                                          |
|----------------------|--------------------------------------------------------------------------|
| SKU                  | SMT750IC                                                                 |
| Product Description: | APC Smart-UPS SMT750IC - UPS - 500 Watt - 750 VA - with APC SmartConnect |
| Device Type:         | UPS - external                                                           |
| Weight:              | 13.18 kg                                                                 |
| Input Voltage:       | AC 220/230/240 V                                                         |
| Output Voltage:      | AC 230 V ± 5%                                                            |
| Power Capacity:      | 500 Watt / 750 VA                                                        |
| Input Connectors:    | 1 x power IEC 60320 C14                                                  |

## General

|               |                  |
|---------------|------------------|
| Device Type:  | UPS - external   |
| Colour:       | Black            |
| Bundled with: | APC SmartConnect |

## Power Device

|                                   |                                          |
|-----------------------------------|------------------------------------------|
| UPS Technology:                   | Line interactive                         |
| Input Voltage:                    | AC 220/230/240 V                         |
| Input Voltage Range:              | AC 160 - 286 V                           |
| Input Voltage Range (Adjustable): | AC 151 - 302 V                           |
| Frequency Provided:               | 50/60 Hz ± 3Hz                           |
| Frequency Required:               | 50/60 Hz ± 3Hz                           |
| Input Connectors:                 | 1 x power IEC 60320 C14                  |
| Power Output Connectors Details:  | 6 x power IEC 60320 C13   2 x IEC jumper |
| Output Voltage:                   | AC 230 V ± 5% - 50/60 Hz                 |
| Power Capacity:                   | 500 Watt / 750 VA                        |
| Output Waveform:                  | Sinewave                                 |
| Surge Suppression:                | Yes                                      |
| Surge Energy Rating:              | 540 Joules                               |
| Circuit Protection:               | Circuit breaker                          |

## Dimensions & Weight (Shipping)

|                  |          |
|------------------|----------|
| Shipping Width:  | 27.8 cm  |
| Shipping Depth:  | 39.9 cm  |
| Shipping Height: | 30.1 cm  |
| Shipping Weight: | 14.23 kg |

## Dimensions & Weight

|         |          |
|---------|----------|
| Width:  | 13.8 cm  |
| Depth:  | 35.81 cm |
| Height: | 15.75 cm |
| Weight: | 13.18 kg |

## Environmental Parameters

|                            |         |
|----------------------------|---------|
| Min Operating Temperature: | 0 °C    |
| Max Operating Temperature: | 40 °C   |
| Humidity Range Operating:  | 0 - 95% |
| Sound Emission:            | 40 dBA  |

## Manufacturer Warranty

|                    |                                                                                         |
|--------------------|-----------------------------------------------------------------------------------------|
| Service & Support: | Limited warranty - replace or repair - 3 years   Limited warranty - batteries - 2 years |
|--------------------|-----------------------------------------------------------------------------------------|

## Battery

|                   |                                                                                                                                                                 |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Quantity:         | 1                                                                                                                                                               |
| Technology:       | Lead Acid                                                                                                                                                       |
| Run Time (Up To): | 4.6 min at full load   15.9 min at half load   103 min at 50 Watts   50.5 min at 100 Watts   21.7 min at 200 Watts   12 min at 300 Watts   7.3 min at 400 Watts |
| Recharge Time:    | 3 hours                                                                                                                                                         |
| Transfer Time:    | 6 ms                                                                                                                                                            |
| Features:         | Maintenance free, sealed, leak-proof                                                                                                                            |

## Networking

|                              |             |
|------------------------------|-------------|
| Remote Management Interface: | RS-232, USB |
|------------------------------|-------------|

## Expansion / Connectivity

|                  |                                                        |
|------------------|--------------------------------------------------------|
| Interfaces:      | 1 x management (RS-232) - RJ-45   1 x management (USB) |
| Expansion Slots: | 1 (total) / 1 (free) x SmartSlot                       |

## Software / System Requirements

|                    |                                 |
|--------------------|---------------------------------|
| Software Included: | APC PowerChute Business Edition |
|--------------------|---------------------------------|

## Miscellaneous

|                      |                                                                                                                                                                                  |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cables Included:     | Serial cable - external   USB cable - external   Power cable 1.83 m                                                                                                              |
| Features:            | Audible alarm, LCD display, Automatic Voltage Regulation (AVR), cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre |
| Compliant Standards: | CSA, UL 1778, VDE, IEC 62040-2, RoHS, REACH, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1                                                                                       |

