

APC Switched Rack PDU 2G Zero U - power distribution strip



Not in stock

SKU	AP8958
Product Description:	APC Switched Rack PDU 2G Zero U - power distribution strip
Device Type:	Power distribution strip - rack-mountable
Weight:	3.2 kg
Input Voltage:	AC 200/208/230 V
Output Voltage:	AC 200/208/230 V
Input Connectors:	1 x power IEC 60320 C20
Output connectors:	1 x power IEC 60320 C19 7 x power IEC 60320 C13

General

Device Type:	Power distribution strip - rack-mountable
Colour:	Black

Power Device

Input Voltage:	AC 200/208/230 V
Input Voltage Range:	AC 100 - 240 V
Frequency Required:	50/60 Hz
Input Connectors:	1 x power IEC 60320 C20
Power Output Connectors Details:	1 x power IEC 60320 C19 7 x power IEC 60320 C13
Output Voltage:	AC 200/208/230 V
Max Electric Current:	16 A

Networking

Remote Management Interface:	RS-232
Remote Management Protocol:	SNMP, Telnet, HTTP

Expansion / Connectivity

Interfaces:	1 x management
-------------	----------------

Miscellaneous

Cables Included:	Power cable Serial cable - external
------------------	---------------------------------------

Compatibility Information

P/N: AP6221CH, AR2200, AR2280, AR2487G, AR3100G, AR3100TAA, AR3100W, AR3103SP, AR3105SP, AR3105W, AR3106SP, AR3107G, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3180G, AR3300G, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR3357X674, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, DLT3000RMI2U, NBES0302, NBPDO160A, NBPDO180, NBWL0355A, NBWL0356A, SMC1000-BR, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I, SMC2000I-2U, SMC3000I, SMC3000RMI2U, SMT1500RM1U, SMT2200I-AR, SMT2200IC, SMT2200R2I-AR, SMT2200RM2UC, SMT2200RMI2UC, SMT2200RMI2UNC, SMT3000I2U-BR, SMT3000I-AR, SMT3000IC, SMT3000R2I-6W, SMT3000R2I-AR, SMT3000RM2UC, SMT3000RMI2UC, SMT3000RMI2UNC, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LVNCUS, SMX2000LVUS, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMHV2U, SMX2200RMLVUS, SMX3000HV-BR, SMX3000HVT, SMX3000HVTUS, SMX3000LV2U-BR, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750C, SMX750CNC,

Miscellaneous

Rack Mounting Kit:	Included
--------------------	----------

Features:	LCD display
-----------	-------------

Compliant Standards:	UL, cUL, EN 61000-3-2, EN55022, ICES-003, VDE, VCCI Class A ITE, EN 61000-3-3, EN55024, RoHS, FCC Part 15 A, PSE Mark, REACH
----------------------	--

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	5 - 95%

Dimensions & Weight

Width:	5.6 cm
Depth:	4.6 cm
Height:	98.8 cm
Weight:	3.2 kg

Dimensions & Weight (Shipping)

Shipping Width:	16.5 cm
Shipping Depth:	11.4 cm
Shipping Height:	113 cm
Shipping Weight:	4.8 kg

Compatibility Information

SMX750US, SPD10KCBL, SPD20KCBL, SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT1000RMXLI-NC, SRT10KRMXLI, SRT10KRMXLT-IEC, SRT10KXLI, SRT10KXLT-IEC, SRT10RMXLIX806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT1500XLI, SRT2200RMXLI, SRT2200RMXLI-NC, SRT2200XLI, SRT2200XLI-KR, SRT3000RMXLI, SRT3000RMXLI-NC, SRT3000RMXLW-IEC, SRT3000XLI, SRT3000XLW-IEC, SRT5KRMXLI, SRT5KRMXLI-6W, SRT5KRMXLIM, SRT5KRMXLT, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-HW, SRT5KRMXLW-TW, SRT5KXLI, SRT6KRMXLI, SRT6KRMXLI-6W, SRT6KRMXLIM, SRT6KRMXLT, SRT6KRMXLT-IEC, SRT6KXLI, SRT6KXLT-IEC, SRT8KRMXLI, SRT8KRMXLT, SRT8KRMXLT-IEC, SRT8KXLI, SRT8KXLT-IEC, SUA2200ICH-45, SUA3000ICH-45, SUA3000I-IN, SURT3000XLI-ET, SURT5000XLIX438, SURTD5000XLI-ET, SYAF16KRMICH, SYAF8KRMTX424