

APC Switched Rack PDU 2G Zero U - power distribution unit



Not in stock

SKU	AP8941
Product Description:	APC Switched Rack PDU 2G Zero U - power distribution unit
Device Type:	Power distribution unit - rack-mountable
Weight:	7.64 kg
Localisation:	Japan, Canada, United States
Input Voltage:	AC 200/208/230 V
Output Voltage:	AC 200/208 V
Input Connectors:	1 x power NEMA L6-30

General

Device Type:	Power distribution unit - rack-mountable
Colour:	Black
Localisation:	Japan, Canada, United States

Power Device

Input Voltage:	AC 200/208/230 V
Frequency Required:	50/60 Hz
Input Connectors:	1 x power NEMA L6-30
Power Output Connectors Details:	3 x power IEC 60320 C19 21 x power IEC 60320 C13
Output Voltage:	AC 200/208 V
Max Electric Current:	30 A

Networking

Remote Management Interface:	Ethernet, RS-232, USB
Remote Management Protocol:	SNMP, Telnet, HTTP

Expansion / Connectivity

Interfaces:	1 x management (Ethernet) - RJ-45 1 x management (RS-232) 1 x management (USB)
-------------	--

Miscellaneous

Cables Included:	Power cable - external - 3.05 m Serial cable - external
------------------	---

Compatibility Information

P/N:	AP4431, AP7950B, AR2200, AR2280, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3100G, AR3100TAA, AR3100W, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3180G, AR3300G, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR3357X674, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBES0302, NBPDO160A, NBPDO180, NBWL0355A, NBWL0356A, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RM2U, SMT1500RM1U, SMT1500RM2U, SMT1500RM1IU, SMT2200RM2UC, SMT3000I2U-BR, SMT3000RM2UC, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LV, SMX2000LVNC, SMX2000LVNCUS, SMX2000LVUS, SMX2200HV, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMHV2U, SMX2200RMLVUS, SMX3000HV, SMX3000HV-BR, SMX3000HVNC, SMX3000HVT, SMX3000HVTUS, SMX3000LV, SMX3000LV2U-BR, SMX3000LVNC, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750C, SMX750CNC,
------	--

Miscellaneous

Rack Mounting Kit:	Included
Features:	LCD display, current meter, LED indicators, overload protection
Compliant Standards:	UL, cUL, ICES-003, VCCI Class A ITE, RoHS, FCC Part 15 A, PSE Mark, REACH

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	5 - 95%

Dimensions & Weight

Width:	5.6 cm
Depth:	4.6 cm
Height:	182.9 cm
Weight:	7.64 kg

Dimensions & Weight (Shipping)

Shipping Width:	16.5 cm
Shipping Depth:	12.4 cm
Shipping Height:	204 cm
Shipping Weight:	10 kg

Compatibility Information

SMX750-NMC, SMX750US, SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT10KRMXLI, SRT10KRMXLT, SRT10KRMXLT-10KTF, SRT10KRMXLT30, SRT10KRMXLT-5KTF2, SRT10KXLT, SRT10KXLT30, SRT10KXLT-5KTF2, SRT10KXLTUS, SRT10KXLTW, SRT10RMXLIX806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT3000RMXLT, SRT3000RMXLT-5KTF, SRT3000RMXLT-NC, SRT3000XLT, SRT3000XLT-5KTF, SRT3000XLTW, SRT5KRMXLT, SRT5KRMXLT-5KTF, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-HW, SRT5KRMXLW-TW, SRT5KXLJ, SRT5KXLT, SRT5KXLT-5KTF, SRT5KXLTUS, SRT6KRMXLI, SRT6KRMXLT, SRT6KRMXLT-5KTF, SRT6KRMXLT-IEC, SRT6KXLT, SRT6KXLT-5KTF, SRT6KXLTUS, SRT6KXLTW, SRT8KRMXLI, SRT8KRMXLT, SRT8KRMXLT30, SRT8KRMXLT-5KTF, SRT8KRMXLT-IEC, SRT8KXLJ, SRT8KXLT, SRT8KXLT30, SRT8KXLT-5KTF, SRT8KXLT-IEC, SRT8KXLTUS, SRT3000XLI-ET, SRT5000XLIX438, SYAF16KRMICH