

APC Switched Rack PDU AP7902B - power distribution unit - 2880 VA



SKU	AP7902B
Product Description:	APC Switched Rack PDU AP7902B - power distribution unit - 2880 VA
Device Type:	Power distribution unit - rack-mountable
Cord Length:	3.05 m
Rack Size:	2U
Weight:	4.5 kg
Input Voltage:	AC 100/120 V
Output Voltage:	AC 120 V

General

Device Type:	Power distribution unit - rack-mountable
Height (Rack Units):	2U
Cord Length:	3.05 m
Colour:	Black

Power Device

Input Voltage:	AC 100/120 V
Input Voltage Range:	AC 100 - 120 V
Frequency Required:	50/60 Hz
Input Connectors:	1 x power NEMA L5-30P
Output Voltage:	AC 120 V
Max Electric Current:	30 A
Power Capacity:	2880 VA

Networking

Remote Management Protocol:	SNMP, Telnet
-----------------------------	--------------

Miscellaneous

Cables Included:	Power cable - integrated - 3.05 m
Rack Mounting Kit:	Included

Compatibility Information

P/N: ACDC2513, AP7950B, AR106, AR106SH4, AR106SH6, AR109SH4, AR109SH6, AR112, AR112SH4, AR112SH6, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3003, AR3003SP, AR3006, AR3006SP, AR3100G, AR3100TAA, AR3100W, AR3103, AR3103SP, AR3105SP, AR3105W, AR3106, AR3106SP, AR3107G, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3180G, AR3300G, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR3357X674, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, AR8213, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBES0302, NBPDO160A, NBPDO180, NBWL0355A, NBWL0356A, SCL400RMJ1U, SCL500RM1UC, SCL500RM1UNC, SCL500RM1IUC, SCL500RM1IUNC, SMC1000-BR, SMC1000I, SMC1000I-2U, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-BR, SMC1500I, SMC1500I-2U, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I-2U, SMC3000RM12U, SMT1500RM1U, SMT1500RM2U, SMT1500RM1IUC, SMT2200RM2UC, SMT3000I2U-BR, SMT3000RM2UC,

Designed For:

Miscellaneous

Compliant Standards: CSA, UL, cUL, ICES-003, UL 60950, IC, FCC Part 15 A

Manufacturer Warranty

Service & Support: Limited warranty - 2 years

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	0 - 95%

Dimensions & Weight

Width:	44.5 cm
Depth:	11.4 cm
Height:	8.9 cm
Weight:	4.5 kg

Dimensions & Weight (Shipping)

Shipping Width:	50.8 cm
Shipping Depth:	36.8 cm
Shipping Height:	14 cm
Shipping Weight:	6.55 kg

Compatibility Information

SMTL1000RM2UC, SMTL1000RMI2UC, SMTL750RM2UC, SMTL750RMI2UC, SMX1000C, SMX1000US, SMX1500RM2UC, SMX1500RM2UCNC, SMX1500RMNCUS, SMX1500RMUS, SMX2000LV, SMX2000LVNC, SMX2000LVNCUS, SMX2000LVUS, SMX2200HV, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMHV2U, SMX2200RMLVUS, SMX3000HV, SMX3000HV-BR, SMX3000HVNC, SMX3000HVT, SMX3000HVTUS, SMX3000LV, SMX3000LV2U-BR, SMX3000LVNC, SMX3000LVNCUS, SMX3000LVUS, SMX3000RMLVUS, SMX3KRMLVNCUS, SMX750C, SMX750CNC, SMX750-NMC, SMX750US, SRT1000RMXLA, SRT1000RMXLA-NC, SRT1000RMXLI, SRT10KRMXLI, SRT10RMXLIX806, SRT1500RMXLA, SRT1500RMXLA-NC, SRT5KRMXLT, SRT5KRMXLT-IEC, SRT5KRMXLTUS, SRT5KRMXLW-HW, SRT5KRMXLW-TW, SRT6KRMXLI, SRT6KRMXLT, SRT6KRMXLT-IEC, SRT8KRMXLI, SRT8KRMXLT, SRT8KRMXLT-IEC, SURT3000XLI-ET, SURT5000XLIX438, SYAF16KRMICH