

APC Switched Rack PDU - power distribution strip



Not in stock

SKU	AP7953
Product Description:	APC Switched Rack PDU - power distribution strip
Device Type:	Power distribution strip - rack-mountable
Rack Size:	0U
Weight:	7 kg
Input Wiring:	3-phase
Input Voltage:	AC 230 V
Input Connectors:	1 x power IEC 60309

General

Device Type:	Power distribution strip - rack-mountable
Height (Rack Units):	0U
Colour:	Black

Power Device

Input Voltage:	AC 230 V
Input Voltage Range:	AC 220 - 240 V
Input Wiring:	3-phase
Frequency Required:	47 - 63 Hz
Input Connectors:	1 x power IEC 60309
Power Output Connectors Details:	21 x power IEC 60320 C13 ; 3 x power IEC 60320 C19
Max Electric Current:	16 A

Networking

Remote Management Interface:	Ethernet
Remote Management Protocol:	SNMP, Telnet, HTTP

Expansion / Connectivity

Interfaces:	1 x management (Ethernet) - RJ-45 ; 1 x management ; 1 x USB - 4 pin USB Type A ; 2 x peripheral
-------------	--

Miscellaneous

Compatibility Information

P/N: SCL400RMJ1U, SCL500RM1UC, SCL500RM1UNC, SMC1000-2U, SMC1000-2UC, SMC1000-2UTW, SMC1000I-2U, SMC1000I-2UC, SMC1500-2U, SMC1500-2UC, SMC1500-2UTW, SMC2000I-2U, SMC2000I2U-BR, SMC3000RM12U, SMT1000R2I-AR, SMT1000RM2UC, SMT1000RM12UC, SMT1200RMJ1U, SMT1500R2I-6W, SMT1500R2I-AR, SMT1500R2-NMC, SMT1500R2X122, SMT1500R2X180, SMT1500RM1U, SMT1500RM2U, SMT1500RM2UC, SMT1500RM2UNC, SMT1500RM2UTW, SMT1500RMI1U, SMT1500RMI2UC, SMT1500RMI2UNC, SMT1500RMJ2U, SMT1500RMUS, SMT2200I2U-BR, SMT2200R2I-AR, SMT2200R2X106, SMT2200RM2UC, SMT2200RM2UNC, SMT2200RM2UTW, SMT2200RMI2UC, SMT2200RMI2UNC, SMT2200RMUS, SMT3000I2U-BR, SMT3000R2I-6W, SMT3000R2I-AR, SMT3000R2X145, SMT3000R2X180, SMT3000RM2UC, SMT3000RM2UNC, SMT3000RM2UTW, SMT3000RMI2UC, SMT3000RMI2UNC, SMT3000RMJ2U, SMT3000RMUS, SMT750R2X122, SMT750RM2UC, SMT750RM2UNC, SMT750RMI2UC, SMT750RMI2UNC, SMTL1000RM2UC, SMTL750RM2UC, SMX1000US, SMX1500RMNCUS, SMX1500RMUS, SMX2000LV, SMX2000LVNC, SMX2000LVNCUS, SMX2000LVUS, SMX2200HV, SMX2200HVNC, SMX2200RMHV2U, SMX2200RMLVUS, SMX2KR2UNCX145, SMX2KRMLVNCUS, SMX3000HV, SMX3000HVNC, SMX3000HVT, SMX3000HVTUS,

Miscellaneous

Cables
Included: Power cable 1.83 m | Serial cable

Rack
Mounting
Kit: Included

Features: LCD display, LED indicator

Compliant
Standards: UL, cUL, EN 61000-3-2, EN55022, VDE, EN 61000-3-3, EN55024, ICES-003 Class A, RoHS, FCC Part 15 A, REACH

Manufacturer Warranty

Service &
Support: Limited warranty - parts and labour - 2 years

Environmental Parameters

Min Operating
Temperature: -5 °C

Max Operating
Temperature: 45 °C

Humidity Range Operating: 5 - 95% (non-condensing)

Dimensions & Weight

Width: 5.6 cm

Depth: 4.6 cm

Height: 179 cm

Weight: 7 kg

Dimensions & Weight (Shipping)

Shipping Width: 16.5 cm

Shipping Depth: 11.4 cm

Shipping Height: 200 cm

Shipping Weight: 8.95 kg

Compatibility Information

SMX3000LV, SMX3000LVNC,
SMX3000LVNCUS, SMX3000LVUS,
SMX3000RMJ2U, SMX3000RMLVUS,
SMX3KRMLVNCUS, SMX750INC, SMX750NC,
SMX750-NMC, SMX750US, SRC2000XLI-CC,
SRC3000XLI-CC, SRT10KRMXLI,
SRT10KRMXLT, SRT10KRMXLT-10KTF,
SRT10KRMXLT30, SRT10KRMXLT-5KTF2,
SRT10KRMXLT-IEC, SRT10RMXLIX806,
SRT2200RMXLA, SRT2200RMXLA-NC,
SRT2200RMXLAUS, SRT2200RMXLI,
SRT2200RMXLI-NC, SRT3000RMXLA,
SRT3000RMXLA-NC, SRT3000RMXLI,
SRT3000RMXLI-NC, SRT3000RMXLT,
SRT3000RMXLT-5KTF, SRT3000RMXLT-NC,
SRT3000RMXLW-IEC, SRT5KRMXLI,
SRT5KRMXLI-6W, SRT5KRMXLIM,
SRT5KRMXLT, SRT5KRMXLT-5KTF,
SRT5KRMXLT-IEC, SRT5KRMXLTUS,
SRT5KRMXLW-HW, SRT5KRMXLW-TW,
SRT6KRMXLI, SRT6KRMXLI-6W,
SRT6KRMXLIM, SRT6KRMXLT, SRT6KRMXLT-
5KTF, SRT6KRMXLT-IEC, SRT8KRMXLI,
SRT8KRMXLT, SRT8KRMXLT30,
SRT8KRMXLT-5KTF, SRT8KRMXLT-IEC,
SUA1000RM2UTW, SUA2200RM2UTW,
SURT1000RMXLI-NC, SYA12K16RMICH,
SYAF16KRMICH