

APC Switched Rack PDU Zero U - power distribution strip



In Stock(6)

SKU	AP7950B
Product Description:	APC Switched Rack PDU Zero U - power distribution strip
Device Type:	Power distribution strip - rack-mountable
Cord Length:	3.05 m
Weight:	4.32 g
Input Voltage:	AC 200/208/230 V
Output Voltage:	AC 230 V
Input Connectors:	1 x power IEC 60320 C14

General

Device Type:	Power distribution strip - rack-mountable
Cord Length:	3.05 m
Colour:	Black

Power Device

Input Voltage:	AC 200/208/230 V
Input Voltage Range:	AC 200 - 240 V
Input Connectors:	1 x power IEC 60320 C14
Power Output Connectors Details:	16 x power IEC 60320 C13
Output Voltage:	AC 230 V
Max Electric Current:	10 A

Networking

Remote Management Interface:	Ethernet 10/100
Remote Management Protocol:	SNMP, Telnet, HTTP

Expansion / Connectivity

Interfaces:	1 x management (Ethernet) - RJ-45 1 x serial - RJ-11
-------------	--

Miscellaneous

Compatibility Information

P/N: AR3355W, AR3357X674, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4038IX432, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBPD0160A, NBWLO355A, NBWLO356A, SCL400RM1U, SCL500RM1UC, SCL500RM1UNC, SCL500RM1UC, SCL500RM1UNC, SMC1000-2UC, SMC1000-2UTW, SMC1000-BR, SMC1000I-2UC, SMC1000I-BR, SMC1000IC, SMC15002U-BR, SMC1500-2UC, SMC1500-2UTW, SMC1500-BR, SMC1500I2U-BR, SMC1500I-2UC, SMC1500I-BR, SMC1500IC, SMC2000I2U-BR, SMT1000I-AR, SMT1000IC, SMT1000R2I-AR, SMT1000RM2UC, SMT1000RM2UC, SMT1500I-AR, SMT1500IC, SMT1500R2I-AR, SMT1500RM2UC, SMT1500RM2UNC, SMT1500RM2UC, SMT1500RM2UNC, SMT2200I2U-BR, SMT2200I-AR, SMT2200IC, SMT2200R2I-AR, SMT2200RM2UC, SMT2200RM2UNC, SMT2200RM2UC, SMT2200RM2UNC, SMT30002U-BR, SMT3000I2U-BR, SMT3000I-AR, SMT3000IC, SMT3000R2I-AR, SMT3000RM2UC, SMT3000RM2UNC, SMT3000RM2UC, SMT3000RM2UNC, SMT750RM2UC, SMT750RM2UNC, SMT750RM2UC, SMT750RM2UNC, SMTL1000RM2UC, SMTL750RM2UC, SMTL750RM2UC, SMX1000US, SMX1500RMNCUS, SMX1500RMUS, SMX2000LVNCUS, SMX2000LVUS, SMX2200HVNC, SMX2200R2HVNC, SMX2200RMLVUS, SMX2KR2UNCX145, SMX2KRMLVNCUS, SMX3000HV-BR, SMX3000HVTUS, SMX3000LV2U-BR, SMX3000LVNCUS, SMX3000LVUS,

Miscellaneous

Cables
Included: Power cable 3.05 m

Rack
Mounting
Kit: Included

Features: LED display, current meter

Compliant
Standards: GOST, EN 61000-3-2, VDE, EN 61000-3-3,
EN55024, IRAM, RoHS, REACH, EN 55022
Class A

Manufacturer Warranty

Service & Support: Limited warranty - parts and labour -
2 years

Environmental Parameters

Min Operating Temperature: -5 °C

Max Operating Temperature: 45 °C

Humidity Range Operating: 0 - 95%

Dimensions & Weight

Width: 5.6 cm

Depth: 4.4 cm

Height: 124.5 cm

Weight: 4.32 g

Dimensions & Weight (Shipping)

Shipping Width: 15.2 cm

Shipping Depth: 12.7 cm

Shipping Height: 213.4 cm

Shipping Weight: 5.23 kg

Compatibility Information

SMX3000RMLVUS, SMX3KRMLVNCUS,
SMX750INC, SMX750NC, SMX750US,
SRC2000XLI-CC, SRC3KUXI, SRT1000RMXLA,
SRT1000RMXLA-NC, SRT1000RMXLI,
SRT1000RMXLI-NC, SRT10KRMXLT-10KTF,
SRT10KRMXLT30, SRT10KRMXLT-5KTF2,
SRT10RMXLIX806, SRT1500RMXLA,
SRT1500RMXLA-NC, SRT1500RMXLI,
SRT1500XLI, SRT2200RMXLA,
SRT2200RMXLA-NC, SRT2200RMXLAUS,
SRT2200RMXLI, SRT2200RMXLI-NC,
SRT2200XLI, SRT2200XLI-KR,
SRT3000RMXLA, SRT3000RMXLA-NC,
SRT3000RMXLI, SRT3000RMXLI-NC,
SRT3000RMXLT, SRT3000RMXLT-5KTF,
SRT3000RMXLT-NC, SRT3000RMXLW-IEC,
SRT3000XLI, SRT3000XLW-IEC,
SRT5KRMXLIM, SRT5KRMXLT-5KTF,
SRT5KRMXLTUS, SRT5KRMXLW-TW,
SRT6KRMXLIM, SRT6KRMXLT-5KTF,
SRT8KRMXLT30, SRT8KRMXLT-5KTF,
SUA1000ICH-45, SUA1000RM2UTW,
SUA1500I-IN, SUA2200ICH-45,
SUA2200RM2UTW, SUA3000I-IN,
SURT1000RMXLI-NC, SURT1000XLI-NC,
SYAF16KRMICH