


ASUS PRIME H410M-D - motherboard - micro ATX - LGA1200 Socket - H410



06-06-2024

SKU	90MB13U0-M0EAY0
Product Description:	ASUS PRIME H410M-D - motherboard - micro ATX - LGA1200 Socket - H410
Product Type:	Motherboard - micro ATX
Chipset Type:	Intel H410
Processor Socket:	1 x LGA1200 Socket
Compatible Processors:	(supports 10th Generation Intel Core / Pentium Gold / Celeron)
Max RAM Size:	64 GB
RAM Supported:	2 DIMM slots - DDR4, non-ECC, unbuffered

General

Product Type:	Motherboard - micro ATX
Chipset Type:	Intel H410
Processor Socket:	LGA1200 Socket
Max Processors Qty:	1
Compatible Processors:	(supports 10th Generation Intel Core / Pentium Gold / Celeron)

Supported RAM

Max Size:	64 GB
Technology:	DDR4
Bus Clock:	2400 MHz, 2133 MHz, 2800 MHz, 2666 MHz, 2933 MHz
Supported RAM Integrity Check:	Non-ECC
Registered or Buffered:	Unbuffered
Features:	Dual channel memory architecture, Intel Extreme Memory Profiles (XMP)

Audio

Type:	HD Audio (8-channel)
-------	----------------------

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Miscellaneous

Included Accessories:	I/O back plate, 1 x M.2 anchor
Cables Included:	2 x Serial ATA cable
Software Included:	ASUS AI Charger, ASUS CPU-Z, ASUS AI Suite III, ASUS EZ Update, ASUS EZ Flash 3, DAEMON Tools, WinRAR, Norton AntiVirus (60 days trial)

Width:	22.6 cm
Depth:	20.1 cm

Features

BIOS Type:	AMI
BIOS Features:	UEFI BIOS
Sleep / Wake Up:	Wake on LAN (WOL), wake on PME

Audio

Audio Codec:	Realtek ALC887
Compliant Standards:	High Definition Audio

LAN

Network Controller:	Realtek RTL8111H
Network Interfaces:	Gigabit Ethernet

Features

Hardware Features:	Jack retasking, ASUS Q-Design, ASUS TurboV EVO, Q-DIMM, ASUS EZ DIY, Q-Slot, CrashFree BIOS 3, audio jack detect technology, ASUS EPU (Energy Processing Unit), ASUS Fan Xpert, Intel Turbo Boost Technology 2.0, ASUS DIGI+ VRM, Preboot eXecution Environment (PXE), ASUS Stainless Steel Back I/O, LANGuard, ASUS Overvoltage Protection, ASUS 5X Protection III, ASUS SafeSlot Core, Intel Turbo Boost Max Technology 3.0, ASUS OptiMem, Armoury Crate
--------------------	--

Expansion / Connectivity

Expansion Slots:	1 x CPU 2 x DIMM 288-pin 1 x PCIe 3.0 x16 2 x PCIe 3.0 x1
Storage Interfaces:	SATA-600 -connectors: 4 x 7pin Serial ATA SATA-600 / PCIe 3.0 -connectors: 1 x M.2
Interfaces:	1 x VGA 1 x HDMI 2 x USB 3.2 Gen 1 4 x USB 2.0 1 x audio line-out - mini-jack 1 x microphone - mini-jack 1 x audio line-in - mini-jack 1 x PS/2 keyboard / mouse 1 x serial 1 x LAN (Gigabit Ethernet)
Internal Interfaces:	2 x USB 2.0 - header 2 x USB 3.2 Gen 1 - header 1 x SPDIF out - header 1 x parallel - header 1 x speaker - header 1 x audio - header
Power Connectors:	24-pin main power connector, 8-pin ATX12V connector

