

ASUS Pro A520M-C/CSM - motherboard - micro ATX - Socket AM4 - AMD A520



23-05-2024

SKU	90MB1550-M0EAYC
Product Description:	ASUS Pro A520M-C/CSM - motherboard - micro ATX - Socket AM4 - AMD A520
Product Type:	Motherboard - micro ATX
Chipset Type:	AMD A520
Processor Socket:	1 x Socket AM4
Compatible Processors:	Ryzen (supports 3rd Generation Ryzen / 3rd Generation Ryzen with Radeon Graphics)
Max RAM Size:	64 GB
RAM Supported:	2 DIMM slots - DDR4, non-ECC, ECC, unbuffered

General

Product Type:	Motherboard - micro ATX
Chipset Type:	AMD A520
Processor Socket:	Socket AM4
Max Processors Qty:	1
Compatible Processors:	Ryzen (supports 3rd Generation Ryzen / 3rd Generation Ryzen with Radeon Graphics)

Supported RAM

Max Size:	64 GB
Technology:	DDR4
Bus Clock:	2400 MHz, 2133 MHz, 2800 MHz, 3000 MHz, 2666 MHz, 3333 MHz (O.C.), 3466 MHz (O.C.), 3733 MHz (O.C.), 3600 MHz (O.C.), 3866 MHz (O.C.), 4000 MHz (O.C.), 4400 MHz (O.C.), 4600 MHz (O.C.), 3200 MHz
Supported RAM Integrity Check:	Non-ECC, ECC

Miscellaneous

Included Accessories:	1 x M.2 screw, I/O back cover
Cables Included:	2 x Serial ATA cable
Software Included:	Drivers & Utilities, ASUS Control Center
Width:	24.4 cm
Depth:	22.9 cm

Features

BIOS Type:	AMI
BIOS Features:	UEFI BIOS
Sleep / Wake Up:	Wake on LAN (WOL), wake on PME
Hardware Features:	Jack retasking, ASUS Q-Design, Q-DIMM, ASUS EZ DIY, Q-Slot, audio jack detect technology, Preboot eXecution Environment (PXE), overcurrent protection, LANGuard, Moistureproof PCB, ASUS Self Recovering BIOS, ASUS Event Log, ASUS Commercial BIOS kit, ASUS Control Center Express (ACC Express)

Expansion / Connectivity

Supported RAM

Registered or Buffered: Unbuffered

Features: Dual channel memory architecture

Audio

Type: HD Audio (8-channel)

Audio Codec: Realtek ALC887

Compliant Standards: High Definition Audio

LAN

Network Controller: Realtek RTL8111H

Network Interfaces: Gigabit Ethernet

Expansion / Connectivity

Expansion Slots: 1 x CPU | 2 x DIMM 288-pin | 1 x PCIe 3.0 x16 | 2 x PCIe 3.0 x1 | 1 x PCI

Storage Interfaces: SATA-600 -connectors: 4 x 7pin Serial ATA - RAID 0 / RAID 1 / RAID 10 | SATA-600 / PCIe 3.0 -connectors: 1 x M.2

Interfaces: 1 x VGA | 1 x DVI-D | 4 x USB 3.2 Gen 1 | 2 x USB 2.0 | 1 x HDMI | 1 x audio line-out - mini-jack | 1 x microphone - mini-jack | 1 x audio line-in - mini-jack | 1 x PS/2 keyboard | 1 x PS/2 mouse | 1 x LAN (Gigabit Ethernet) | 1 x serial

Internal Interfaces: 4 x USB 2.0 - header | 2 x USB 3.2 Gen 1 - header | 1 x parallel - header | 1 x serial - header | 1 x speaker - header | 1 x audio - header

Power Connectors: 24-pin main power connector, 8-pin ATX12V connector

