

ASUS ROG STRIX B660-A GAMING WIFI D4 - motherboard - ATX - LGA1700 Socket - B660



Not in stock

| | |
|------------------------|--|
| SKU | 90MB1850-M1EAY0 |
| Product Description: | ASUS ROG STRIX B660-A GAMING WIFI D4 - motherboard - ATX - LGA1700 Socket - B660 |
| Product Type: | Motherboard - ATX |
| Chipset Type: | Intel B660 |
| Processor Socket: | 1 x LGA1700 Socket |
| Compatible Processors: | (supports 12th and 13th Generation Intel Core / Pentium Gold / Celeron) |
| Max RAM Size: | 128 GB |
| RAM Supported: | 4 DIMM slots - DDR4, non-ECC, unbuffered |

General

| | |
|------------------------|---|
| Product Type: | Motherboard - ATX |
| Chipset Type: | Intel B660 |
| Processor Socket: | LGA1700 Socket |
| Max Processors Qty: | 1 |
| Compatible Processors: | (supports 12th and 13th Generation Intel Core / Pentium Gold / Celeron) |

Supported RAM

| | |
|-------------|--|
| Max Size: | 128 GB |
| Technology: | DDR4 |
| Bus Clock: | 2400 MHz, 2133 MHz, 2800 MHz, 3000 MHz, 2666 MHz, 2933 MHz, 3400 MHz (O.C.), 3333 MHz (O.C.), 3466 MHz (O.C.), 3733 MHz (O.C.), 3600 MHz (O.C.), 4000 MHz (O.C.), 4400 MHz (O.C.), 4266 MHz (O.C.), 4600 MHz (O.C.), 4800 MHz (O.C.), 3200 MHz, 5000 MHz (O.C.), 5333 MHz (O.C.) |

Manufacturer Warranty

Service & Support: Limited warranty - 3 years

Miscellaneous

| | |
|-----------------------|---|
| Included Accessories: | Cable ties, STRIX stickers, ROG thank you card, ROG key chain, ASUS Wi-Fi moving aerial, 1 x M.2 rubber package, M.2 Q-Latch |
| Cables Included: | 4 x Serial ATA cable |
| Software Included: | ROG CPU-Z, ASUS AI Suite III, ASUS Turbo App, Antivirus, Sonic Studio Virtual Mixer, ROG GameFirst VI, AIDA64 Extreme (60 days trial), ASUS AURA Creator, Sonic Suite Companion, MyAsus, Armoury Crate, Sonic Studio III, Sonic Radar III, ASUS Fan Xpert 4 |
| Compliant Standards: | VCCI Class B ITE, JATE, WEEE, FCC Part 15 Class B, EU RoHS, EU REACH |
| Width: | 30.5 cm |
| Depth: | 24.4 cm |

Features

| | |
|------------|-----|
| BIOS Type: | AMI |
|------------|-----|

Produktdatablad genereret d. 18-10-2024 08:20.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

Supported RAM

Supported RAM Integrity Check: Non-ECC

Registered or Buffered: Unbuffered

Features: Dual channel memory architecture, Intel Extreme Memory Profiles (XMP)

Audio

Type: HD Audio (8-channel)

Audio Codec: SupremeFX (ALC4080)

Compliant Standards: High Definition Audio, DTS Sound Unbound

LAN

Network Interfaces: 2.5 Gigabit Ethernet, 802.11a/b/g/n/ac/ax, Bluetooth 5.2

Expansion / Connectivity

Expansion Slots: 1 x CPU ; 4 x DIMM 288-pin ; 1 x PCIe 5.0 x16 ; 1 x PCIe 3.0 x16 (x4 mode) ; 2 x PCIe 3.0 x1 ; 2 x M.2 socket (2242/2260/2280 M.2 Key M slot) ; 1 x M.2 socket (2242/2260/2280/22110 M.2 Key M slot)

Storage Interfaces: SATA-600 -connectors: 4 x 7pin Serial ATA - RAID 0 / RAID 1 / RAID 10 / RAID 5 ; PCIe 4.0 -connectors: 3 x M.2

RAID Features: Intel Rapid Storage Technology

Interfaces: 1 x HDMI ; 1 x DisplayPort ; 1 x LAN (2.5Gigabit Ethernet) ; 1 x USB-C 3.2 Gen2x2 ; 4 x USB 2.0 ; 1 x USB 3.2 Gen 2 ; 2 x USB 3.2 Gen 1 ; 1 x USB-C 3.2 Gen 1 ; 1 x audio line-in - mini-jack ; 1 x audio line-out (rear) - mini-jack ; 1 x audio line-out (center/subwoofer) - mini-jack ; 1 x audio line-out - mini-jack ; 1 x microphone - mini-jack ; 2 x aerial

Internal Interfaces: 3 x USB 2.0 - header ; 2 x USB 3.2 Gen 1 - header ; 1 x USB-C 3.2 Gen 2 - header ; 1 x audio - header ; 1 x Thunderbolt - header ; 1 x SPDIF out - header ; 1 x SPI - header

Power Connectors: 4-pin ATX12V connector, 24-pin main power connector, 8-pin ATX12V connector

Features

BIOS Features: UEFI BIOS, ASUS EZ Flash 3

Sleep / Wake Up: Wake on LAN (WOL), wake on PME

Hardware Features: Jack retasking, ASUS Q-Design, ASUS TurboV EVO, Q-DIMM, ASUS EZ DIY, Q-LED, Q-Slot, ASUS Extreme Engine Digi+, CrashFree BIOS 3, audio jack detect technology, ASUS DIGI+ VRM, SupremeFX Shielding technology, Preboot eXecution Environment (PXE), LANGuard, 6 Layer PCB, ASUS SafeSlot, Intel Optane Memory Ready, ASUS SafeDIMM, M.2 heatsink, ASUS ProCool, Water Pump Header, pre-mounted I/O shield, ASUS Aura Sync, ASUS OptiMem II, 12+1 Phase Power Design, DIY Friendly Design, FlexKey button, Savitech SV3H712 amplifier, M.2 Q-Latch, 5K Black Metallic Capacitors, Windows 11 compatible, CPU Socket lever protector, VRM heatsink design, BIOS FlashBack button, BIOS FlashBack LED

e

Produktdatablad genereret d. 18-10-2024 08:20.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.