

ASUS RS300-E11-RS4 - rack-mountable - no CPU - 0 GB - no HDD



Not in stock

SKU	90SF01Y1-M000E0
Product Description:	ASUS RS300-E11-RS4 - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	1-way
Processor:	No CPU
Processor Socket:	LGA1200 Socket
RAM:	0 GB (installed) / 128 GB (max) - DDR4 SDRAM

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Server Scalability:	1-way
Front Accessible Bays Qty:	1
Hot-Swap Bays Qty:	4

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	1
CPU Upgradability:	Upgradable
CPU Socket:	LGA1200 Socket
Chipset Type:	Intel C252

RAM

Installed Size:	0 GB / 128 GB (max)
Technology:	DDR4 SDRAM
Form Factor:	DIMM 288-pin
Slots:	4 (Total) / 4 (empty)
Features:	Unbuffered, dual channel memory architecture

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	35 °C

Dimensions & Weight

Width:	43.95 cm
Depth:	49.7 cm
Height:	4.4 cm

Operating System / Software

OS Provided:	No operating system
--------------	---------------------

Power

Device Type:	Power supply
Power Redundancy:	Yes
Power Redundancy Scheme:	1+1
Installed Qty:	2
Max Supported Qty:	2
Voltage Required:	AC 100-240 V (50 - 60 Hz)
Power Provided:	450 Watt
80 PLUS Certification:	80 PLUS Platinum

Hard Drive

Type: No HDD

Storage Controller

Type: 1 x SATA

Channel Qty: 6

RAID Level: RAID 0, RAID 1, RAID 5, RAID 10

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Graphics Controller

Graphics Processor: ASPEED AST2600

Video Memory: 64 MB

Video Interfaces: VGA

Networking

Ethernet Ports: 2 x Gigabit Ethernet

Ethernet Controller: 2 x Intel I210-AT

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Miscellaneous

Included Accessories: VROC module

Compliant Standards: FCC Class A certified, BSMI

Expansion / Connectivity

Bays: 1 (total) / 1 (free) x external 5.25" Slim Line
; 4 (total) / 4 (free) x hot-swap 3.5"

Slots: 1 (total) / 1 (free) x PCIe 4.0 x16 - half-length, full-height (x16 mode (x8 mode if PCI Express 4.0 x8 slot is occupied)) ; 1 (total) / 1 (free) x PCIe 4.0 x8 - half-length, half-height ; 1 (total) / 1 (free) x PCIe 3.0 x4

Interfaces: 2 x USB 3.2 Gen 1 (2 in front) ; 2 x LAN (Gigabit Ethernet) - RJ-45 ; 2 x USB 3.2 Gen 2 ; 1 x management - RJ-45 ; 2 x VGA (1 front, 1 rear) ; 1 x HDMI ; 1 x serial

