

ASUS RS500A-E9-RS4-U - rack-mountable - no CPU - 0 GB - no HDD



Not in stock

SKU	90SF00M1-M00180
Product Description:	ASUS RS500A-E9-RS4-U - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	1-way
Processor:	No CPU
Processor Socket:	Socket SP3
RAM:	0 GB (installed) / 2048 GB (max) - DDR4 SDRAM

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Server Scalability:	1-way
Front Accessible Bays Qty:	1
Hot-Swap Bays Qty:	4

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	35 °C

Dimensions & Weight (Shipping)

Shipping Weight:	17 kg
------------------	-------

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	1
CPU Upgradability:	Upgradable
CPU Socket:	Socket SP3

Dimensions & Weight

Width:	44.4 cm
Depth:	61.6 cm
Height:	4.4 cm
Weight:	11 kg

RAM

Installed Size:	0 GB / 2048 GB (max)
Technology:	DDR4 SDRAM
Form Factor:	DIMM 288-pin
Slots:	16 (Total) / 16 (empty)
Features:	Registered, Load-Reduced DIMM (LRDIMM), 3DS Load-Reduced DIMM (LRDIMM)

Power

Device Type:	Power supply
Power Redundancy:	Yes
Power Redundancy Scheme:	1+1
Installed Qty:	2
Max Supported Qty:	2
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Provided:	770 Watt
80 PLUS Certification:	80 PLUS Platinum

RAM

RAM Supported:	2048 GB Load-Reduced
----------------	----------------------

Hard Drive

Type:	No HDD
-------	--------

Storage Controller

Type:	1 x SATA
-------	----------

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	None.
---------------	-------

Graphics Controller

Graphics Processor:	ASPEED AST2500
Video Memory:	64 GB
Video Interfaces:	VGA

Networking

Ethernet Ports:	2 x Gigabit Ethernet
Ethernet Controller:	Intel I350-AM2
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet

Miscellaneous

Included Accessories:	ASMB9-iKVM Remote Management Card
Compliant Standards:	FCC Class A certified, BSMI

Expansion / Connectivity

Bays:	1 (total) / 1 (free) x external 5.25" Slim Line ; 4 (total) / 4 (free) x hot-swap 2.5" / 3.5" shared
Slots:	1 (total) / 1 (free) x PCIe 3.0 x16 - half-length, full-height ; 1 (total) / 1 (free) x PCIe 3.0 x8 - half-length, full-height ; 1 (total) / 1 (free) x PCIe 3.0 x8 / Open Compute Project mezzanine (OCP) 2.0 ; 1 (total) / 1 (free) x M.2 Card
Interfaces:	4 x USB 3.0 (2 front, 2 rear) ; 2 x LAN (Gigabit Ethernet) ; 2 x VGA (1 front, 1 rear) ; 1 x management

