

ASUS TS300-E10-PS4 - tower - no CPU - 0 GB - no HDD



23-05-2024

SKU	90SF00S1-M01570
Product Description:	ASUS TS300-E10-PS4 - tower - no CPU - 0 GB - no HDD
Type:	Server - tower
Height (Rack Units):	5U
Server Scalability:	1-way
Processor:	No CPU
Processor Socket:	LGA1151 Socket
RAM:	0 GB (installed) / 128 GB (max) - DDR4 SDRAM

General

Type:	Server
Product Form Factor:	Tower - 5U
Server Scalability:	1-way
Front Accessible Bays Qty:	3
Hot-Swap Bays Qty:	4

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	35 °C

Dimensions & Weight (Shipping)

Shipping Weight:	18.9 kg
------------------	---------

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	1
CPU Upgradability:	Upgradable
CPU Socket:	LGA1151 Socket
Chipset Type:	Intel C246

Dimensions & Weight

Width:	21.75 cm
Depth:	54.5 cm
Height:	45.5 cm
Weight:	15 kg

RAM

Installed Size:	0 GB / 128 GB (max)
Technology:	DDR4 SDRAM
Form Factor:	DIMM 288-pin
Slots:	4 (Total) / 4 (empty)
Features:	Unbuffered, dual channel memory architecture

Operating System / Software

OS Provided:	No operating system
--------------	---------------------

Power

Device Type:	Power supply
Voltage Required:	AC 100-240 V (50/60 Hz)
Power Provided:	500 Watt
80 PLUS Certification:	80 PLUS Gold

Hard Drive

Miscellaneous

Compliant Standards:	FCC Class A certified, BSMI
----------------------	-----------------------------

Hard Drive

Type: No HDD

Storage Controller

Type: 1 x RAID

Controller Interface Type: SATA 6Gb/s

Channel Qty: 4

RAID Level: RAID 0, RAID 1, RAID 5, RAID 10

Optical Storage

Type: No optical drive

Monitor

Monitor Type: None.

Graphics Controller

Graphics Processor: ASPEED AST2500

Video Memory: 64 MB

Video Interfaces: VGA

Networking

Ethernet Ports: 4 x Gigabit Ethernet

Ethernet Controller: 4 x Intel I210-AT

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Expansion / Connectivity

Bays: 4 (total) / 4 (free) x hot-swap 2.5" / 3.5" shared ; 3 (total) / 3 (free) x external 5.25"

Slots: 1 (total) / 1 (free) x PCIe 3.0 x16 (x16/x8 mode) ; 1 (total) / 1 (free) x PCIe 3.0 x8 ; 1 (total) / 1 (free) x PCIe 3.0 x8 (x4 mode) ; 2 (total) / 2 (free) x M.2 Card - 22110 ; 1 (total) / 1 (free) x PCI ; 1 (total) / 1 (free) x MIO

Interfaces: 4 x LAN (Gigabit Ethernet) ; 1 x management - RJ-45 ; 2 x USB 2.0 (2 in front) ; 1 x VGA ; 1 x serial ; 4 x USB 3.2 Gen 1 (2 front, 2 rear) ; 1 x USB - Type A (1 internal) ; 2 x USB 3.2 Gen 2

