

ASUS TUF Gaming B650M-Plus WIFI - motherboard - micro ATX - Socket AM5 - AMD B650



01-10-2024

SKU	90MB1BF0-M0EAY0
Product Description:	ASUS TUF Gaming B650M-Plus WIFI - motherboard - micro ATX - Socket AM5 - AMD B650
Product Type:	Motherboard - micro ATX
Chipset Type:	AMD B650
Processor Socket:	1 x Socket AM5
Compatible Processors:	Ryzen (supports Ryzen 7000 Series)
Max RAM Size:	128 GB
RAM Supported:	4 DIMM slots - DDR5, non-ECC, ECC, on-die ECC, unbuffered

General

Product Type:	Motherboard - micro ATX
Chipset Type:	AMD B650
Processor Socket:	Socket AM5
Max Processors Qty:	1
Compatible Processors:	Ryzen (supports Ryzen 7000 Series)

Supported RAM

Max Size:	128 GB
Technology:	DDR5
Bus Clock:	5200 MHz (O.C.), 5400 MHz (O.C.), 5600 MHz (O.C.), 5800 MHz (O.C.), 6000 MHz (O.C.), 4800 MHz, 6200 MHz (O.C.), 6400 MHz (O.C.), 5000 MHz
Supported RAM Integrity Check:	Non-ECC, ECC, on-die ECC
Registered or Buffered:	Unbuffered
Features:	Dual channel memory architecture, AMD EXPO technology

Miscellaneous

Included Accessories:	ASUS Wi-Fi moving aerial, 2 x M.2 rubber package, M.2 screw package
Cables Included:	2 x Serial ATA cable
Software Included:	ASUS AI Suite III, PC Cleaner, WinRAR, ASUS TUF GAMING CPU-Z, Norton AntiVirus (Trial), ASUS AURA Creator, MyAsus, Armoury Crate, ASUS Fan Xpert 2+
Compliant Standards:	VCCI Class B ITE, JATE, WEEE, FCC Part 15 Class B, DisplayPort 1.4, EU RoHS, EU REACH
Width:	24.4 cm
Depth:	24.4 cm

Features

BIOS Type:	AMI
BIOS Features:	UEFI BIOS, ASUS EZ Flash 3

Audio

Type:	HD Audio (8-channel)
Compliant Standards:	High Definition Audio

LAN

Network Interfaces:	2.5 Gigabit Ethernet, Bluetooth 5.2
---------------------	-------------------------------------

Features

Hardware Features:	Jack retasking, ASUS Q-Design, 12+2 Phase Power Design, ESD Guards, ASUS TurboV EVO, Q-DIMM, ASUS EZ DIY, Q-LED, Q-Slot, CrashFree BIOS 3, audio jack detect technology, ASUS DIGI+ VRM, ASUS Stainless Steel Back I/O, TUF LANGuard, TUF Components, overvoltage protection, ASUS SafeDIMM, M.2 heatsink, ASUS ProCool, Water Pump Header, pre-mounted I/O shield, ASUS TUF Protection, ASUS Aura Sync, ASUS OptiMem II, ASUS SafeSlot Core+, M.2 Q-Latch, VRM heatsink design, BIOS FlashBack button, BIOS FlashBack LED, 60A Power Stage
--------------------	---

Expansion / Connectivity

Expansion Slots:	1 x CPU ; 4 x DIMM 288-pin ; 1 x PCIe 4.0 x16 ; 1 x PCIe 4.0 x16 (x4 mode) ; 1 x PCIe 4.0 x1 ; 2 x M.2 socket (2242/2260/2280 M.2 Key M slot)
------------------	---

Storage Interfaces:	SATA-600 -connectors: 4 x 7pin Serial ATA - RAID 0 / RAID 1 / RAID 10 ; PCIe 4.0 - connectors: 1 x M.2 - RAID 0 / RAID 1 / RAID 10 ; PCIe 5.0 -connectors: 1 x M.2 - RAID 0 / RAID 1 / RAID 10
---------------------	--

Interfaces:	1 x HDMI ; 1 x DisplayPort ; 1 x USB-C 3.2 Gen2x2 ; 2 x USB 3.2 Gen 2 ; 1 x USB 3.2 Gen 1 ; 4 x USB 2.0 ; 2 x aerial ; 1 x audio line-in - mini-jack ; 1 x audio line-out - mini-jack ; 1 x microphone - mini-jack ; 1 x audio line-out (center/subwoofer) - mini-jack ; 1 x audio line-out (rear) - mini-jack ; 1 x LAN (2.5Gigabit Ethernet)
-------------	--

Internal Interfaces:	1 x USB-C 3.2 Gen 1 - header ; 2 x USB 3.2 Gen 1 - header ; 4 x USB 2.0 - header ; 1 x audio - header ; 1 x Thunderbolt - header ; 1 x serial - header
----------------------	--

Power Connectors:	4-pin ATX12V connector, 24-pin main power connector, 8-pin ATX12V connector
-------------------	---

