ASUS WS C246 PRO - motherboard - ATX - LGA1151 Socket - C246



Not in stock

SKU	90SW00G0-M0EAY0
Product Description:	ASUS WS C246 PRO - motherboard - ATX - LGA1151 Socket - C246
Product Type:	Motherboard - ATX
Chipset Type:	Intel C246
Processor Socket:	1 x LGA1151 Socket
Compatible Processors:	Pentium, Celeron, Core i5, Core i3, Core i7, Xeon E3-2100 series
Max RAM Size:	64 GB
RAM Supported:	4 DIMM slots - DDR4, non-ECC, ECC, unbuffered

General

Product Type:	Motherboard - ATX
Chipset Type:	Intel C246
Processor Socket:	LGA1151 Socket
Max Processors Qty:	1
Compatible Processors:	Pentium, Celeron, Core i5, Core i3, Core i7, Xeon E3-2100 series

Supported RAM

Max Size:	64 GB
Technology:	DDR4
Bus Clock:	2400 MHz, 2133 MHz, 2666 MHz
Supported RAM Integrity Check:	Non-ECC, ECC
Registered or Buffered:	Unbuffered
Features:	Dual channel memory architecture

Audio

Type:	HD Audio (8-channel)
Audio Codec:	Realtek ALC887
Compliant Standards:	High Definition Audio

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years

Miscellaneous

Included Accessories:	I/O back plate
Software Included:	Drivers & Utilities, ASUS Control Center
Width:	30.5 cm
Depth:	24.4 cm

Features

BIOS Type:	AMI
BIOS Features:	WfM 2.0 support, ASUS EZ Flash, USB BIOS Flashback, ACPI 5.0a support, DMI 3.0 support, SMBIOS 3.0 support
Hardware Monitoring:	CPU core temperature, CPU fan tachometer, chassis fan tachometer
Sleep / Wake Up:	Wake on LAN (WOL), wake on ring (WOR), wake on PME
Hardware Features:	CrashFree BIOS 3, Intel Turbo Boost Technology, Dual LAN Teaming, AMD 3-way CrossFireX technology support, Preboot eXecution Environment (PXE), ASUS SafeSlot

Dette dokument genereret d. 27-04-2024 09:48.
Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

LAN

Network Controller:	Intel I210-AT / I219LM
Network Interfaces:	2 x Gigabit Ethernet

Expansion / Connectivity

Expansion Slots:	1 x CPU ¦ 4 x DIMM 288-pin ¦ 1 x PCIe 3.0 x16 (x16/x8 mode) ¦ 1 x PCIe 3.0 x16 (x8 mode) ¦ 2 x PCIe 3.0 x16 (x4 mode) ¦ 2 x PCIe 3.0 x1
Storage Interfaces:	SATA-600 -connectors: 8 x 7pin Serial ATA - RAID 0 / RAID 1 / RAID 10 / RAID 5 ¦ SATA-600 / PCIe 3.0 -connectors: 2 x M.2
Interfaces:	2 x LAN (Gigabit Ethernet) ¦ 1 x USB 3.1 Gen 2 ¦ 1 x USB-C Gen2 ¦ 4 x USB 3.1 Gen 1 ¦ 1 x HDMI ¦ 1 x DisplayPort ¦ 1 x DVI-D ¦ 1 x VGA ¦ 1 x audio line-out (center/subwoofer) - mini-jack ¦ 1 x audio line-out (rear) - mini-jack ¦ 1 x audio line-in - mini-jack ¦ 1 x audio line-out - mini-jack ¦ 1 x microphone - mini-jack ¦ 1 x TOSLINK
Internal Interfaces:	4 x USB 2.0 - header ¦ 2 x USB 3.1 Gen 1 - header ¦ 1 x serial - header ¦ 1 x SPDIF out - header ¦ 1 x audio - header
Power Connectors:	24-pin main power connector, 8-pin ATX12V connector, 6-pin ATX12V connector