

Axis C1004-E - IP speaker - for PA system



31-05-2024

SKU	0923-001
Product Description:	Axis C1004-E - IP speaker - for PA system
Product Type:	IP speaker - for PA system
Media Content Source:	Flash memory card
Protection:	Splashproof
Enclosure Design:	Bass reflex
Speaker Type:	2-way - active
Continuous Power:	6 Watt



General

Product Type:	IP speaker - for PA system
Media Content Source:	Flash memory card
Microphone:	Yes
Protection:	Splashproof
Enclosure Colour:	Black
Enclosure Design:	Bass reflex
Enclosure Material:	Plastic, metal

Speaker System

Speaker Type:	2-way - active
Continuous Power:	6 Watt
Frequency Response:	60 - 20000 Hz
Max Output Level (Max SPL):	96 dB
Amplifier:	Integrated
Amplifier Class:	D
Amplifier Output Power:	6W
Coverage:	130° x 100°
Interfaces:	IEEE 802.3af (Power over Ethernet)
VoIP Protocols:	SIP
Audio Formats:	WAV, PCM, MP3, ADPCM

Speaker System Details

Driver Details:	Speaker: woofer driver - 4.72" Speaker: tweeter driver - 0.98" - balanced dome
-----------------	--

Connections

Connector Type:	LAN (RJ-45)
-----------------	-------------

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Dimensions & Weight

Width:	19.6 cm
Depth:	20 cm
Height:	29 cm
Weight:	3 kg

Power

Power Source:	Power over Ethernet (PoE)
---------------	---------------------------

Miscellaneous

Included Accessories:	Mounting hardware, mounting bracket, AVHS authentication key, AXIS Camera Station licence key, cable shoe, AXIS Connector Guard A
Compliant Standards:	EN 61000-3-2, EN 61000-3-3, EN55024, EN 61000-6-1, ICES-003 Class A, EN 61000-6-2, NEMA Type 3R, FCC Part 15 B Class A, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, EN 50121-4, IEC 62236-4, VCCI Class A, KN24, EN 55022 Class A, IEC EN60529, KN35, AS/NZS CISPR 32 Class A, EN 55032 Class A, KCC KN32 Class A, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22