

Axis C1410 - IP speaker - for PA system



In Stock(10)

SKU	02838-001
Product Description:	Axis C1410 - IP speaker - for PA system
Product Type:	IP speaker - for PA system
Features:	DSP
Integrated Memory:	Flash - 512 MB
Speaker Type:	Active
Frequency Response:	100 - 20000 Hz
Amplifier Output Power:	7W - D

General

Product Type:	IP speaker - for PA system
Features:	DSP
Integrated Memory:	Flash - 512 MB
Microphone:	Yes
Sensors:	Motion sensor
Enclosure Colour:	White
Enclosure Material:	Plastic
Design Features:	Paintable

Compatibility Information

Designed For: P/N: 02723-002, 02723-004

Manufacturer Warranty

Service & Support: Limited warranty - 5 years

Dimensions & Weight

Diameter:	18.2 cm
Height:	5.2 cm
Weight:	600 g

Power

Power Source: Power over Ethernet (PoE)

Miscellaneous

Included AVHS authentication key, AXIS Camera Accessories: Station licence key

Compliant Standards:	EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, FCC Part 15 B, EN 61000-6-2, IP40, VCCI Class B, EN 55032 Class B, AS/NZS CISPR 32 Class B, EN 55035, IEC/EN/UL 62368-1, CAN ICES-3(B)/NMB3(B), IEEE 802.1x
----------------------	---

Connections

Connector Type: LAN (RJ-45)

Speaker System Details

Speaker System Details

Driver Details: Speaker: full-range driver - 2.5"

Speaker System

Speaker Type:	Active
Frequency Response:	100 - 20000 Hz
Max Output Level (Max SPL):	90 dB
Amplifier:	Integrated
Amplifier Class:	D
Amplifier Output Power:	7W
Coverage:	145°
Interfaces:	IEEE 802.3 (Ethernet), IEEE 802.3u (Fast Ethernet), IEEE 802.3af (Power over Ethernet)
VoIP Protocols:	SRTP, SIP over TLS, SIPS
Voice Codecs:	Speex, Opus, L16, PCMA, PCMU, G.726-32
Network Protocols:	TCP, UDP, ICMP, ARP, HTTP, DNS, SNMP, HTTPS, NTP
Audio Formats:	WAV, PCM, G.726, MP3, ADPCM, AAC-LC, G.711

