

AXIS P3807-PVE Network Camera - panoramic camera - dome



Not in stock

SKU	01048-001
Product Description:	AXIS P3807-PVE Network Camera - panoramic camera - dome
Device Type:	Panoramic camera - fixed - dome
Audio:	Yes
Dimensions (WxDxH):	20.6 cm 16.6 cm
Weight:	1.6 kg
Colour:	White
Connectivity Technology:	Wired

General

Device Type:	Panoramic camera
Audio Support:	Yes
Form Factor:	Dome
Connectivity Technology:	Wired
Width:	20.6 cm
Height:	16.6 cm
Weight:	1.6 kg

Camera

Type:	Colour - fixed
Digital Video Format:	MJPEG, H.264, AVC
Max Digital Video Resolution:	4320 x 1920
Motion Detection:	Yes
Video Modes:	4K
Exposure Range:	1/10 sec - 1/33500 sec
Minimum Illumination:	0.17 lux - colour - F2.0 ; 0.05 lux - B&W - F2.0

Environmental Parameters

Min Operating Temperature:	-30 °C
Max Operating Temperature:	50 °C
Relative Humidity (operating):	10 - 100% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Software / System Requirements

Software Included:	Windows decoder 1-user licence
--------------------	--------------------------------

Power

Power Requirements:	PoE Class 3
Power Device:	12.9 Watt

Miscellaneous

Included Accessories:	Mounting bracket, AXIS U-shape conduit adapter, weathershield, Resistorx L-key, cable gasket
-----------------------	--

Camera

Digital Video Capture Resolution: 480 x 270, 4320 x 1920

Frame Rate (max): 30 frames per second

RAM: 1024 MB

Flash Memory: 512 MB

Features: Sharpness control, white balance, saturation control, brightness control, contrast control, infrared cut filter, Privacy Mask Function, Lightfinder technology, active tampering alarm, password protection, noise reduction, Zipstream technology, panoramic view, image overlay, exposure control, Pixel Counter Support, digest authentication, Forensic WDR, IP address filtering, HTTPs encryption

Image Sensor

Type: 8.3 MP RGB BSI CMOS 1/2.9"

Lens Construction

Type: Fixed focal

Focal Length: 3.2 mm

Lens Iris: F/2.0

Horizontal Field of View (degree): 180 - 90

Panning

Range (degree): -180 to +180

Miscellaneous

Compliant Standards: EN55024, EN 61000-6-1, ICES-003 Class A, EN 61000-6-2, IEC 60068-2-27, IP67, IK10, FCC Part 15 B Class A, IP66, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, EN 50121-4, IEC 62236-4, VCCI Class A, IEC EN60529, KN35, NEMA250 Type 4X, AS/NZS CISPR 32 Class A, KN32 Class A, EN 55032 Class A, IEC/EN/UL 60950-22, IEC/EN/UL 62368-1, IEEE 802.1x

Colour: White

Expansion / Connectivity

Ports: LAN/power - RJ-45

Supported Memory Cards: microSD Card, microSDHC Card, microSDXC Card

Interfaces

Network Interface: Ethernet 10Base-T/100Base-TX/1000Base-T

Network Protocols: DHCP, DNS, FTP, HTTP, NTP, SMTP, TCP/IP, UDP/IP, ARP, ICMP, SNMP 1, SNMP 2c, SNMP 3, SOCKS, RTSP, RTP, HTTPS, UPnP, TLS, IPv6, Bonjour, RTCP, SMB, IGMP, SSH, SSL, QOS, CIFS, SFTP, LLDP