

Axis XC1311 - IP speaker - for PA system



05-11-2024

SKU	02962-001
Product Description:	Axis XC1311 - IP speaker - for PA system
Product Type:	IP speaker - for PA system
Features:	DSP
Integrated Memory:	Flash - 1024 MB
Protection:	Impact protection, dustproof, water-resistant
Enclosure Design:	Horn
Speaker Type:	Active

General

Product Type:	IP speaker - for PA system
Features:	DSP, AXIS Audio Manager Edge
Integrated Memory:	Flash - 1024 MB
Protection:	Impact protection, dustproof, water-resistant
Enclosure Colour:	RAL 3000
Enclosure Design:	Horn
Enclosure Material:	Aluminium
Design Features:	Swivel design

Environmental Parameters

Min Operating Temperature:	-40 °C
Max Operating Temperature:	60 °C
Min Storage Temperature:	-40 °C
Max Storage Temperature:	65 °C
Humidity Range Operating:	10 - 100% RH (condensing)
Humidity Range Storage:	5 - 95% RH (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years
--------------------	----------------------------

Dimensions & Weight

Diameter:	22 cm
Depth:	33.5 cm
Weight:	4.22 kg

Power

Power Source:	Power over Ethernet (PoE)
Power Consumption Operational:	7 Watt

Miscellaneous

Produktdatablad genereret d. 22-10-2024 23:35.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

Miscellaneous

Included Accessories: Terminal block, ring terminal connector, AVHS authentication key

Compliant Standards: UL Class I Division 1, ATEX/IECEX Zone 1, EN 55035, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2, FCC Part 15 B Class A, AN/CSA-C22.2 No. 62368-1 (Canada), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529, IP66, IP67, NEMA 250 Type 4X, NIST SP500-267, IEEE 802.3af Class 3

Connections

Connector Type: LAN (RJ-45)

Speaker System Details

Driver Details: Speaker: full-range driver - 2.5" - dynamic cone

Speaker System

Speaker Type: Active

Frequency Response: 280 - 12500 Hz

Max Output Level (Max SPL): 110 dB

Maximum Sampling Rate Supported: 48 kHz

Amplifier: Integrated

Amplifier Class: D

Amplifier Output Power: 7W

Coverage: 100° x 70°

Interfaces: IEEE 802.3 (Ethernet), IEEE 802.3u (Fast Ethernet), IEEE 802.3af (Power over Ethernet)

VoIP Protocols: SRTP, SIP over TLS

Speaker System

Voice Codecs: G.711u-law, G.726

Network Protocols: IPv4, IPv6, ICMP, HTTP, HTTPS, TLS, FTP, SFTP, CIFS, SMB, SMTP, MDNS, UPnP, SNMPv3, DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, DHCP, ARP, SSH, Link Layer Discovery Protocol (LLDP), Cisco Discovery Protocol (CDP), IEEE 802.1x, SNMP

Audio Formats: AAC-LC, G.711, PCM, G.726, ADPCM, U-LAW, WAV, MP3

