

Brother ADS-1200 - document scanner - portable - USB 3.0, USB 2.0 (Host)



In Stock(2)

SKU	ADS1200TC1
Product Description:	Brother ADS-1200 - document scanner - portable - USB 3.0, USB 2.0 (Host)
Device Type:	Document scanner - portable
Interface Type:	USB 3.0, USB 2.0 (Host)
Scanning Sensor Type:	Dual CIS
Additional Functions:	Scan to USB, scan to file, scan to email, scan to OCR, scan to image
Max Supported Document Size:	215.9 x 863 mm
Input Type:	Colour

General

Type:	Document scanner - portable
Interface Type:	USB 3.0, USB 2.0 (Host)
Additional Functions:	Scan to USB, scan to file, scan to email, scan to OCR, scan to image
Max Supported Document Size:	215.9 x 863 mm

Scanner

Input Type:	Colour
Grayscale Depth:	8-bit (256 colours)
Colour Depth:	48-bit colour
Colour Depth (External):	24-bit (16.7 million colours)
Optical Resolution:	600 dpi x 600 dpi
Interpolated Resolution:	1200 dpi x 1200 dpi
Scan Mode:	Single-pass
Automatic Duplexing:	Yes

Environmental Parameters

Sound Emission:	50 dBA
-----------------	--------

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Dimensions & Weight (Shipping)

Shipping Width:	38 cm
Shipping Depth:	15.7 cm
Shipping Height:	20 cm
Shipping Weight:	1.9 kg

Dimensions & Weight

Width:	30 cm
Depth:	10.3 cm
Height:	8.3 cm
Weight:	1.36 kg

Software / System Requirements

Software Included:	Nuance Power PDF, Nuance PaperPort 14 SE
--------------------	--

Scanner

Scanning Sensor Type: Dual CIS

Max Document Scan Speed B/W: 25 ppm

Max Document Scan Speed Colour: 25 ppm

Duty Cycle: 1000 scans per day

Scanner Speed Details: 25 ppm - black & white - A4 | 25 ppm - colour - A4 | 50 ipm - duplex - black & white - A4 | 50 ipm - duplex - colour - A4

Compliant Standards: TWAIN, WIA, SANE, ICA

Media Handling

Max Document Size: 215.9 mm x 863 mm

Supported Document Type: Plain paper, plastic card, receipts

Document Feeder Type: Automatic

Document Storage Capacity: 20 sheets

Software / System Requirements

OS Required: Linux, Microsoft Windows 7 (32/64 bits), Microsoft Windows Server 2008 R2 SP1, Microsoft Windows Server 2012, Windows 8 (32/64 bits), Microsoft Windows Server 2012 R2, Windows 10 (32/64 bits), Microsoft Windows Server 2016, Apple macOS 10.12.x, Apple macOS 10.13.x, Apple MacOS X 10.11.6

Power

Power Device: External power adapter

Voltage Required: AC 120/230 V (50/60 Hz)

Power Consumption Operational (Standby): 8 Watt

Power Consumption Stand by: 3.2 Watt

Power Consumption Sleep: 1.3 Watt

Environmental Standards

ENERGY STAR Certified: Yes

Expansion / Connectivity

Interfaces Details: USB 2.0 (Host) - Type A | USB 3.0 - Micro-B

