

Brother P-Touch PT-D800W - label printer - B/W - thermal transfer



In Stock(9)

SKU	PTD800WZW1
Product Description:	Brother P-Touch PT-D800W - label printer - B/W - thermal transfer
Printer Type:	Label printer - thermal transfer - B/W
Weight:	3.4 kg
Max Media Size:	Roll (3.6cm)
Max Media Size (Custom):	36 mm
Print Speed:	Up to 60 mm/sec
Max Resolution (B&W):	720 x 360 dpi

General

Printer Type:	Label printer - thermal transfer - monochrome
---------------	---

Printer

Print Speed:	Up to 60 mm/sec
--------------	-----------------

Interface:	USB 2.0, Wi-Fi(n)
------------	-------------------

Max Resolution (B&W):	720 x 360 dpi
-----------------------	---------------

Fonts:	Brussels, Florida, Helsinki, US, San Diego, Los Angeles, Calgary, Letter Gothic, Belgium, Atlanta, Adams, Sofia, Brunei, Germany
--------	--

Character Sizes:	9 points, 6 points, 36 points, 24 points, 18 points, 12 points, 10 points, 14 points, 20 points, 28 points, 7 points, 11 points, 5 points, 56 points, 72 points, 48 points, 16 points, 8 points, 64 points, 40 points, 4 points, 22 points, 32 points, 80 points, 88 points, 90 points
------------------	--

Styles & Effects:	Vertical
-------------------	----------

Display Resolution:	4 lines x 17 characters
---------------------	-------------------------

Keyboard:	71 keys
-----------	---------

Repeating Printing:	5000 copies
---------------------	-------------

Dimensions & Weight (Shipping)

Width (Shipping):	38.2 cm
Depth (Shipping):	43.5 cm
Height (Shipping):	29.6 cm
Weight (Shipping):	5.2 kg

Dimensions & Weight

Width:	33.7 cm
Depth:	18.8 cm
Height:	17.3 cm
Weight:	3.4 kg

Environmental Parameters

Min Operating Temperature:	10 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	20 - 80%

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years with product registration - carry-in
--------------------	---

Environmental Standards

ENERGY STAR:	Yes
--------------	-----

Printer

Barcodes:

Code 39, UCC/EAN-128, ISBN, GS1 DataBar, QR code, MaxiCode, Aztec code, UPC-A, UPC-E, Codabar, Code 128, Postnet, PDF417, Data Matrix, GS1 DataBar Omnidirectional, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded, GS1 DataBar Limited, ITF 2 of 5, EAN-8, EAN-13, RSS-14

Printer Features:

Auto Power Off

Media Handling

Media Type:

Laminated tape

Compatible Tapes:

TZe tape, HGe tape, HSe tape, FLe label

Max Media Size:

Roll (3.6cm)

Max Media Size (Custom):

36 mm

Media Sizes:

Roll (2.4 cm), Roll (0.6 cm), Roll (1.8 cm), Roll (1.2 cm), Roll (0.9 cm), Roll (3.6cm), Roll (0.35 cm), Roll (0.58 cm), Roll (2.36 cm), Roll (1.77 cm), Roll (1.17 cm), Roll (0.88 cm), 21 x 45 mm

Media Feeders:

1 x manual - 1 roll - Roll (3.6cm)

Software / System Requirements

OS Required:

Linux, Microsoft Windows Server 2008 R2, Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2012, Windows 8 (32/64 bits), Microsoft Windows Server 2012 R2, Apple MacOS X 10.9.x, Apple MacOS X 10.10.x, Windows 10 (32/64 bits), Apple MacOS X 10.11.x

Power

Power Device:

Power adapter - external

Miscellaneous

Media Included:

1 TZe tape cassette

Expansion / Connectivity

Connections:

1 x USB 2.0

