

Cisco Meraki Cloud Managed MS120-24P - switch - 24 ports - Managed - rack-mountable



Not in stock

SKU	MS120-24P-HW
Product Description:	Cisco Meraki Cloud Managed MS120-24P - switch - 24 ports - Managed - rack-mountable
Device Type:	Switch - 24 ports - Managed
Enclosure Type:	Rack-mountable 1U
Subtype:	Gigabit Ethernet
Ports:	24 x 10/100/1000 + 4 x Gigabit SFP
Power Over Ethernet (PoE):	PoE
PoE Budget:	370 W

General

Device Type: Switch - 24 ports - Managed

Enclosure Type: Desktop, rack-mountable 1U

Subtype: Gigabit Ethernet

Ports: 24 x 10/100/1000 + 4 x Gigabit SFP

Power Over Ethernet (PoE): PoE

PoE Budget: 370 W

Performance: Switching capacity: 56 Gbps | Forwarding rate: 41.67 Mpps

Capacity: VLANs supported: 4094 | MAC forwarding entries: 16000

Jumbo Frame Support: 9578 bytes

Remote Management Protocol: SNMP

Authentication Method: RADIUS

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 40 °C

Humidity Range Operating: 5 - 95% (non-condensing)

Manufacturer Warranty

Service & Support: Limited warranty - advance parts replacement - lifetime - response time: next business day

Dimensions & Weight

Width: 44 cm

Depth: 25 cm

Height: 4.4 cm

Weight: 3.71 kg

Miscellaneous

Rack Mounting Kit: Included

MTBF: 1,700,716 hours

Compliant Standards: CSA, IC, FCC, RoHS, RCM

Power

Produktdatablad genereret d. 23-06-2024 03:26.

Vær opmærksom på at priser og lagerstatus var gældende på genereringstidspunktet og dermed ikke kan garanteres.

General

Features:

Flow control, auto-negotiation, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, Syslog support, port mirroring, E-mail alert, Broadcast Storm Control, firmware upgradable, STP support, RSTP support, DHCP snooping, ACL support, QoS, SMS alert, STP Root Guard, fanless, DHCP client, crossover detection, SSO support, RBAC, Cisco Discovery Protocol, STP BPDU Guard, ZTP, DSCP to CoS Mutation

Compliant Standards:

IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3af, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1ab (LLDP)

Power

Power Device: Internal power supply

Voltage Required: AC 120/230 V (47 - 63 Hz)

Expansion / Connectivity

Interfaces: 24 x 1000Base-T RJ-45 | 4 x 1000Base-T SFP

