

# Cisco Meraki MX68 - security appliance



Not in stock

SKU	MX68-HW
Product Description:	Cisco Meraki MX68 - security appliance
Device Type:	Security appliance
Form Factor:	Desktop
Ports Qty:	10
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Performance:	Firewall throughput: 450 Mbps   VPN throughput: 200 Mbps   Advanced security throughput: 300 Mbps
Capacity:	Maximum number of users: 50

## General

Device Type:	Security appliance
Width:	28.4 cm
Depth:	14.8 cm
Height:	2.7 cm
Weight:	1.12 kg

## Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	5 - 95% (non-condensing)

## Manufacturer Warranty

Service & Support:	Limited warranty - advance hardware replacement - lifetime - response time: next day
--------------------	--

## Power

Power Over Ethernet (PoE) Supported:	PoE+
Power Device:	External power adapter
Installed Qty:	1
Max Supported Qty:	1
Power Provided:	100 Watt

## Expansion / Connectivity

Interfaces:	2 x 1000Base-T - RJ-45 (WAN)   8 x 1000Base-T - RJ-45   2 x 1000Base-T (PoE+) - RJ-45   1 x USB 2.0 - Type A
-------------	--

## Networking

**Form Factor:** Desktop

**Ports Qty:** 10

**Connectivity Technology:** Wireless, wired

**Data Link Protocol:** Ethernet, Fast Ethernet, Gigabit Ethernet

**Network / Transport Protocol:** L2TP, IPSec, PPPoE, DHCP

**Routing Protocol:** Static IP routing, MPLS

**Performance:** Firewall throughput: 450 Mbps | VPN throughput: 200 Mbps | Advanced security throughput: 300 Mbps

**Capacity:** Maximum number of users: 50

**Features:** Firewall protection, DHCP support, NAT support, load balancing, layer 7 switching, VLAN support, traffic shaping, content filtering, Intrusion Detection System (IDS), Intrusion Prevention System (IPS), firmware upgradable, wall mountable, IPSec Virtual Private Network (VPN), Quality of Service (QoS), MPLS VPN, 3G/4G USB Dongle Support, static routing, 802.1x authentication, Link Aggregation, VPN client, IP Security (IPSec) support, DMZ support