

Cisco 1921 - router - desktop, rack-mountable



Not in stock

SKU	CISCO1921/K9-RF
Product Description:	Cisco 1921 - router - desktop, rack-mountable
Device Type:	Router
Enclosure Type:	Desktop, rack-mountable - modular - 1U
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Network / Transport Protocol:	IPSec, L2TPv3
Routing Protocol:	OSPF, IS-IS, BGP, EIGRP, DVMRP, PIM-SM, static IP routing, IGMPv3, GRE, PIM-SSM, static IPv4 routing, static IPv6 routing, policy-based routing (PBR), MPLS
Remote Management Protocol:	SNMP, RMON



General

Device Type: Router

Enclosure Type: Desktop, rack-mountable - modular - 1U

Connectivity Technology: Wired

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet

Network / Transport Protocol: IPSec, L2TPv3

Routing Protocol: OSPF, IS-IS, BGP, EIGRP, DVMRP, PIM-SM, static IP routing, IGMPv3, GRE, PIM-SSM, static IPv4 routing, static IPv6 routing, policy-based routing (PBR), MPLS

Remote Management Protocol: SNMP, RMON

Features: Firewall protection, VPN support, MPLS support, VLAN support, Syslog support, IPv6 support, CBWFQ, WRED, QoS, WSMA, TR-069 Agent, NetFlow

Compliant Standards: IEEE 802.3ah, IEEE 802.1ah, IEEE 802.1ag, VCCI, CISPR 22 Class A, CISPR 24, EN 61000-3-2, EN55024, EN55022 Class A, EN50082-1, AS/NZS 60950-1, CAN/CSA-E60065-00, ICES-003 Class A, CS-03, FCC CFR47 Part 15, UL 60950-1, IEC 60950-1, EN 60950-1, BSMI CNS 13438, CSA C22.2 No. 60950-1, AS/NZS 3548 Class A, EN 300 386

RAM: 512 MB (installed) / 512 MB (max)

Flash Memory: 256 MB (installed) / 256 MB (max)

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 40 °C

Humidity Range Operating: 10 - 85%

Dimensions & Weight

Width: 34.3 cm

Depth: 29.2 cm

Height: 4.4 cm

Weight: 5.4 kg

Software / System Requirements

OS Provided: Cisco IOS IP Base

Miscellaneous

Rack Mounting Kit: Optional

Pricing Type: Refurbished

Power

Power Device: Internal power supply

Voltage Required: AC 120/230 V (50/60 Hz)

Power Consumption Operational: 60 Watt

Expansion / Connectivity

Interfaces: 2 x 10Base-T/100Base-TX/1000Base-T - RJ-45 | Serial: 1 x console | Management: 1 x console - mini-USB Type B | Serial: 1 x auxiliary | USB 2.0: 1 x 4 pin USB Type A

Expansion Slots: 2 (total) / 2 (free) x EHWIC

