

Cisco Catalyst 2960CX-8TC-L - switch - 8 ports - Managed - rack-mountable



Not in stock

SKU	WS-C2960CX-8TC-L
Product Description:	Cisco Catalyst 2960CX-8TC-L - switch - 8 ports - Managed - rack-mountable
Device Type:	Switch - 8 ports - Managed
Enclosure Type:	Rack-mountable 1U
Subtype:	Gigabit Ethernet
Ports:	8 x 10/100/1000 + 2 x SFP + 2 x 10/100/1000 (uplink)
Performance:	Forwarding performance: 12 Gbps Forwarding performance (64-byte packet size): 17.9 Mpps
Capacity:	Virtual interfaces (VLANs): 1023

General

Device Type:	Switch - 8 ports - Managed
Enclosure Type:	Desktop, rack-mountable, DIN rail mountable, wall-mountable 1U
Subtype:	Gigabit Ethernet
Ports:	8 x 10/100/1000 + 2 x SFP + 2 x 10/100/1000 (uplink)
Performance:	Forwarding performance: 12 Gbps Forwarding performance (64-byte packet size): 17.9 Mpps
Capacity:	Virtual interfaces (VLANs): 1023
Jumbo Frame Support:	9018 bytes
Routing Protocol:	RIP-1, RIP-2, static IP routing
Remote Management Protocol:	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTP, TFTP, CLI
Authentication Method:	Kerberos, Secure Shell (SSH), RADIUS, TACACS+
Features:	BOOTP support, ARP support, VLAN support, Syslog support, DiffServ support, IPv6 support, STP support, DHCP snooping, PAgP support, ACL support, QoS, fanless, SRR, MAC Address Notification, RSPAN, Energy Efficient Ethernet, MVR, CoS, WTD

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	5 - 95% (non-condensing)
Min Storage Temperature:	-25 °C
Max Storage Temperature:	70 °C
Humidity Range Storage:	5 - 95% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - advance parts replacement - lifetime - response time: next business day Technical support - consulting - 90 days
--------------------	---

Dimensions & Weight

Width:	26.9 cm
Depth:	21.3 cm
Height:	4.44 cm
Weight:	1.72 kg

Software / System Requirements

General

Compliant Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.3ah, IEEE 802.1ae, IEEE 802.1ab (LLDP), IEEE 802.3az
RAM:	512 MB
Flash Memory:	128 MB
Status Indicators:	Port status, port transmission speed, port duplex mode, system, link/activity

Software / System Requirements

Software Included:	Cisco IOS LAN Base
--------------------	--------------------

Miscellaneous

MTBF:	756,260 hours
Compliant Standards:	GOST, CISPR 24, EN55022, EN55024, CISPR 22, CCC, RoHS, UL 60950-1, IEC 60950-1, EN 60950-1, ANATEL, GB 4943, KCC Class A, IEC 60825, KN22, KN24, VCCI V-3/2007.04 Class A, AS/NZS CISPR22:2004 Class A, CAN/CSA-C22.2 No. 60950-1

Power

Power Device:	Internal power supply
Power Provided:	300 Watt
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Consumption Operational:	16.7 Watt
80 PLUS Certification:	80 PLUS Silver

Expansion / Connectivity

Interfaces:	8 x 1000Base-T RJ-45 1 x console RJ-45 1 x mini-USB Type B management 1 x USB Type A 2 x 1000Base-T RJ-45 uplink 2 x SFP uplink
-------------	---

