

Cisco FirePOWER 1010 Next-Generation Firewall - firewall



In Stock(68)

SKU	FPR1010-NGFW-K9
Product Description:	Cisco FirePOWER 1010 Next-Generation Firewall - firewall
Device Type:	Firewall
Form Factor:	Desktop
Hard Drive:	200 GB x 1
Performance:	Firewall and Application Visibility and Control (AVC) throughput (1024B): 650 Mbps ; Firewall and Application Visibility and Control (AVC) and Intrusion Prevention System (IPS) throughput (1024B): 650 Mbps ; Firewall and Application Visibility and Control (AVC) throughput (450B): 225 Mbps ; Firewall and Application Visibility and Control (AVC) and Intrusion Prevention System (IPS) throughput (450B): 225 Mbps ; Transport Layer Security (TLS) throughput: 150 Mbps ; NGIPS throughput (1024B): 650 Mbps ; NGIPS throughput (450B): 225 Mbps ; IPSec VPN throughput (1024B TCP w/Fastpath): 300 Mbps
Capacity:	Maximum concurrent sessions with AVC: 100000 ; New connections per second with AVC: 6000
Power:	AC 120/230 V (50/60 Hz)



General

Device Type:	Firewall
Width:	19.9 cm
Depth:	20.5 cm
Height:	4.62 cm
Weight:	1.36 kg

Processor / Memory / Storage

Hard Drive:	200 GB x 1
-------------	------------

Networking

Form Factor:	Desktop
Connectivity Technology:	Wired

Performance:

Firewall and Application Visibility and Control (AVC) throughput (1024B): 650 Mbps | Firewall and Application Visibility and Control (AVC) and Intrusion Prevention System (IPS) throughput (1024B): 650 Mbps | Firewall and Application Visibility and Control (AVC) throughput (450B): 225 Mbps | Firewall and Application Visibility and Control (AVC) and Intrusion Prevention System (IPS) throughput (450B): 225 Mbps | Transport Layer Security (TLS) throughput: 150 Mbps | NGIPS throughput (1024B): 650 Mbps | NGIPS throughput (450B): 225 Mbps | IPSec VPN throughput (1024B TCP w/Fastpath): 300 Mbps

Capacity:	Maximum concurrent sessions with AVC: 100000 New connections per second with AVC: 6000
Features:	Fanless

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	90% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - advance hardware replacement - 90 days - response time: 10 days
--------------------	--

Software / System Requirements

Software Included:	Cisco Threat Defense 6.4
--------------------	--------------------------

Power

Power Device:	External power adapter
Voltage Required:	AC 120/230 V (50/60 Hz)

Miscellaneous

Compliant Standards:	CISPR 22 Class A, CISPR 24, EN 61000-3-2, EN 61000-3-3, EN55024, AS/NZS 60950-1, EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, ICES-003 Class A, EN 61000-4-5, EN 61000-4-11, EN 61000-4-8, UL 60950-1, IEC 60950-1, EN 60950-1, GB 4943, Directive 2004/108/EC, VCCI Class A, KN24, KN22 Class A, EN 55022 Class A, FCC CFR47 Part 15 A, CNS 13438 Class A, EN 300 386, TVCN 7317, Directive 2006/108/EC, TCVN 7189, CAN/CSA-C22.2 No. 60950-1, AS/NZS CISPR22 Class A
----------------------	---

Expansion / Connectivity

Interfaces:	8 x - RJ-45 1 x 1000Base-T (management) - RJ-45 1 x serial - RJ-45 1 x USB 3.0 - Type A
-------------	---