

# Cisco FirePOWER 1120 Next-Generation Firewall - firewall



In Stock(1)

<b>SKU</b>	FPR1120-NGFW-K9
<b>Product Description:</b>	Cisco FirePOWER 1120 Next-Generation Firewall - firewall
<b>Device Type:</b>	Firewall
<b>Form Factor:</b>	Rack-mountable - 1U
<b>Hard Drive:</b>	200 GB x 1
<b>Performance:</b>	Firewall and Application Visibility and Control (AVC) throughput (1024B): 1.5 Gbps ; Firewall and Application Visibility and Control (AVC) and Intrusion Prevention System (IPS) throughput (1024B): 1.5 Gbps ; Firewall and Application Visibility and Control (AVC) throughput (450B): 550 Mbps ; Firewall and Application Visibility and Control (AVC) and Intrusion Prevention System (IPS) throughput (450B): 550 Mbps ; Transport Layer Security (TLS) throughput: 700 Mbps ; NGIPS throughput (1024B): 1.5 Gbps ; NGIPS throughput (450B): 550 Mbps ; IPsec VPN throughput (1024B TCP w/Fastpath): 1 Gbps
<b>Capacity:</b>	Maximum concurrent sessions with AVC: 200000 ; New connections per second with AVC: 15000
<b>Included Accessories:</b>	Mounting brackets

## General

Device Type:	Firewall
Height (Rack Units):	1U
Width:	43.7 cm
Depth:	26.9 cm
Height:	4.37 cm
Weight:	3.63 kg

## Processor / Memory / Storage

Hard Drive:	200 GB x 1
-------------	------------

## Networking

Form Factor:	Rack-mountable
--------------	----------------

Connectivity Technology:	Wired
--------------------------	-------

Performance:	Firewall and Application Visibility and Control (AVC) throughput (1024B): 1.5 Gbps ; Firewall and Application Visibility and Control (AVC) and Intrusion Prevention System (IPS) throughput (1024B): 1.5 Gbps ; Firewall and Application Visibility and Control (AVC) throughput (450B): 550 Mbps ; Firewall and Application Visibility and Control (AVC) and Intrusion Prevention System (IPS) throughput (450B): 550 Mbps ; Transport Layer Security (TLS) throughput: 700 Mbps ; NGIPS throughput (1024B): 1.5 Gbps ; NGIPS throughput (450B): 550 Mbps ; IPsec VPN throughput (1024B TCP w/Fastpath): 1 Gbps
--------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Capacity:	Maximum concurrent sessions with AVC: 200000 ; New connections per second with AVC: 15000
-----------	-------------------------------------------------------------------------------------------

Features:	1 fan
-----------	-------

## Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	90% (non-condensing)

## Manufacturer Warranty

Service & Support:	Limited warranty - advance hardware replacement - 90 days - response time: 10 days
--------------------	------------------------------------------------------------------------------------

## Software / System Requirements

Software Included:	Cisco Threat Defense 6.4
--------------------	--------------------------

## Power

Power Device:	Internal power supply
Voltage Required:	AC 120/230 V (50/60 Hz)

## Miscellaneous

Included Accessories:	Mounting brackets
-----------------------	-------------------

Compliant Standards:	CISPR 22 Class A, CISPR 24, EN 61000-3-2, EN 61000-3-3, EN55024, AS/NZS 60950-1, EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, ICES-003 Class A, EN 61000-4-5, EN 61000-4-11, EN 61000-4-8, UL 60950-1, IEC 60950-1, EN 60950-1, GB 4943, Directive 2004/108/EC, VCCI Class A, KN24, KN22 Class A, EN 55022 Class A, FCC CFR47 Part 15 A, CNS 13438 Class A, EN 300 386, TVCN 7317, Directive 2006/108/EC, TCVN 7189, CAN/CSA-C22.2 No. 60950-1, AS/NZS CISPR22 Class A
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Expansion / Connectivity

Interfaces:	8 x - RJ-45 ; 4 x - SFP (mini-GBIC) ; 1 x 1000Base-T (management) - RJ-45 ; 1 x serial - RJ-45 ; 1 x USB 3.0 - Type A
-------------	-----------------------------------------------------------------------------------------------------------------------