

Cisco Integrated Services Router 1101 - router - rack-mountable



In Stock(14)

SKU	C1101-4P
Product Description:	Cisco Integrated Services Router 1101 - router - rack-mountable
Device Type:	Router - 4-port switch (integrated)
Enclosure Type:	Rack-mountable
WAN Ports Qty:	1
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Performance:	Encryption throughput: 350 Mbps
Network / Transport Protocol:	IPSec, PPPoE, DHCP, DNS, L2TPv3

General

Device Type:	Router - 4-port switch (integrated)
Enclosure Type:	Rack-mountable
Connectivity Technology:	Wired
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Performance:	Encryption throughput: 350 Mbps
Network / Transport Protocol:	IPSec, PPPoE, DHCP, DNS, L2TPv3

Routing Protocol:	OSPF, IS-IS, RIP-1, RIP-2, BGP, EIGRP, HSRP, DVMRP, VRRP, PIM-SM, static IP routing, IGMPv3, GRE, PIM-SSM, policy-based routing (PBR), MPLS, Bidirectional Forwarding Detection (BFD), RSVP
-------------------	---

Remote Management Protocol:	SNMP, RMON, CLI, TR-069
-----------------------------	-------------------------

Encryption Algorithm:	DES, Triple DES, SHA, MD5, IKE, ECDSA, 128-bit AES, 256-bit AES, 1024-bit RSA, 2048-bit RSA, 256-bit SHA, 512-bit SHA, 748-bit RSA, 384-bit SHA
-----------------------	---

Authentication Method:	RADIUS
------------------------	--------

Features:	CBWFQ, WRED, ACL support, QoS, DMVPN, NetFlow, MRC, IPFIX, CSD, LISP, packet aggregation A-MPDU, packet aggregation A-MSDU, MIB II, AVC, AAA, DFS, ERSPAN, EEM
-----------	--

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 85% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - advance parts replacement - 1 year - response time: 10 days
--------------------	--

Dimensions & Weight

Width:	19.05 cm
Depth:	15.24 cm
Height:	2.79 cm
Weight:	1.76 kg

Miscellaneous

Rack Mounting Kit:	Optional
--------------------	----------

Power

Power Device:	External power adapter - 30 Watt
Voltage Required:	AC 100-240 V (50/60 Hz)

General

Compliant Standards:

IEEE 802.1Q, IEEE 802.11i, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.11r, EN 61000-3-2, EN55022, ICES-003, EN 61000-3-3, CISPR 22, CB, EN 61000-6-1, EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, EN 61000-4-5, EN 61000-4-11, FCC CFR47 Part 15, UL 60950-1, EN 60950-1, VCCI V-3, IEC 60950-1 Second Edition, AS/NZS CISPR 22, CNS 13438, EN 301 489-7, EN 301 489-1, FCC CFR47 Part 22, FCC CFR47 Part 24, EN 300 386, IEC 60950-1 First Edition, CAN/CSA-C22.2 No. 60950-1, EN 301 489-24, EN 301 908-1, EN 301 908-2, EN 301 511, EN 301 908-13

RAM: 4 GB

Flash Memory: 4 GB

Power

Power Consumption Operational: 30 Watt

Expansion / Connectivity

WAN: 1 x 1000Base-T/1000Base-X - RJ-Interfaces: 45/SFP | LAN: 4 x 1000Base-T - RJ-45 | USB 3.0: 1 x

