

Cisco Integrated Services Router 921 - router - desktop



In Stock(56)

SKU	C921-4P
Product Description:	Cisco Integrated Services Router 921 - router - desktop
Device Type:	Router - 4-port switch (integrated)
Enclosure Type:	Desktop
WAN Ports Qty:	2
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Network / Transport Protocol:	L2TP, RSVP, ICMP/IP, IPSec, FTP, DHCP, DNS, L2TPv3, DDNS, RTP, HTTP, HTTPS, cRTP
Routing Protocol:	OSPF, RIP-1, RIP-2, BGP, EIGRP, HSRP, VRRP, NHRP, IGMPv3, GRE, OSPFv3, policy-based routing (PBR), BGP-4+, WCCP, Bidirectional Forwarding Detection (BFD), RSVP, STP, MGRE

General

Device Type:	Router - 4-port switch (integrated)
Enclosure Type:	Desktop
Connectivity Technology:	Wired
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Network / Transport Protocol:	L2TP, RSVP, ICMP/IP, IPSec, FTP, DHCP, DNS, L2TPv3, DDNS, RTP, HTTP, HTTPS, cRTP
Routing Protocol:	OSPF, RIP-1, RIP-2, BGP, EIGRP, HSRP, VRRP, NHRP, IGMPv3, GRE, OSPFv3, policy-based routing (PBR), BGP-4+, WCCP, Bidirectional Forwarding Detection (BFD), RSVP, STP, MGRE
Remote Management Protocol:	Telnet, SNMP 3, HTTP, HTTPS, SSH, CLI
Encryption Algorithm:	DES, Triple DES, AES, SSL, PKI, 128-bit AES, 192-bit AES, 256-bit AES
Authentication Method:	Secure Shell (SSH), RADIUS, TACACS+

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	5 - 95% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - advance parts replacement - 1 year - response time: 10 days
--------------------	--

Dimensions & Weight

Width:	22.86 cm
Depth:	24.13 cm
Height:	4.32 cm

Software / System Requirements

OS Provided:	Cisco IOS IP Base
--------------	-------------------

Power

General

Features:

NAT support, auto-uplink (auto MDI/MDI-X), IGMP snooping, DiffServ support, MAC address filtering, LLQ, CBWFQ, WFQ, ACL support, QoS, LFI, DMVPN, DHCP server, VRF-Lite, DNS proxy, DHCP relay, DHCP client, MIB, NDP, VPN Server, FNF, DSCP support, Storm Control, SmartPort technology, VPN client, HQoS, SPAN, EEM, MHSRP, NBAR, NBAR 2, Pfr, CBTS, CBTP, CBWRED, Cisco IP SLA, Cisco NG PnP Protocol

Compliant Standards:

IEEE 802.1D, IEEE 802.1Q, IEEE 802.1x, EN 61000-6-1, AS/NZS 60950-1, FCC CFR47 Part 15, UL 60950-1, IEC 60950-1, EN 60950-1, VCCI V-3, EN 61000-3-2:2006, EN 61000-3-3:2008, KN24, CNS13438:2006, EN 300 386 V1.6.1, CISPR 24:2010, EN 55024:2010, CISPR 22:2008, EN 300 386, TCVN 7189, EN 55032, CAN/CSA-C22.2 No. 60950-1, TCVN 7317, KN22:2009, ICES-003:2012 Issue 5

Processor:	2.2 GHz
RAM:	1 GB
Flash Memory:	2 GB

Power

Power Device:	Internal power supply
Voltage Required:	AC 120/230 V (50/60 Hz)

Expansion / Connectivity

Interfaces:	WAN: 2 x 10Base-T/100Base-TX/1000Base-T - RJ-45 LAN: 4 x 10Base-T/100Base-TX/1000Base-T - RJ-45 Management: 1 x console - RJ-45 USB 2.0: 1 x 4 pin USB Type A
-------------	---

