

Cisco - power supply - hot-plug - 750 Watt



SKU	C3K-PWR-750WAC=
Product Description:	Cisco - power supply - hot-plug - 750 Watt
Device Type:	Power supply - hot-plug - plug-in module
Weight:	1.8 kg
Input Voltage:	AC 100-240 V
Power Capacity:	750 Watt
Input Connectors:	Power IEC 60320 C13
Dimensions (WxDxH):	15.2 cm x 29 cm x 4.2 cm

General

Device Type: Power supply - hot-plug - plug-in module

Power Device

Input Voltage:	AC 100-240 V
Frequency Required:	50 - 60 Hz
Input Connectors:	Power IEC 60320 C13
Power Capacity:	750 Watt

Miscellaneous

Compliant Standards:	FCC Class A certified, BSMI, CISPR 22 Class A, GOST, CISPR 24, NOM, VCCI Class A ITE, EN55024, EN55022 Class A, AS/NZS 60950-1, CCC, FCC Part 15, MIC, UL 60950-1, IEC 60950-1, EN 60950-1
----------------------	--

Compatibility Information

Designed For:	Cisco Catalyst 2960-24LC-S, 2960-24LT-L, 2960-24PC-L, 2960-24PC-S, 2960-24-S, 2960-24TC, 2960-24TC-L, 2960-24TC-S, 2960-24TT, 2960-48PST-L, 2960-48PST-S, 2960-48T, 2960-48TC, 2960-48TC-L, 2960-48TC-S, 2960-48TT, 2960-48TT-L, 2960-48TT-S, 2960-8TC, 2960-8TC-S, 2960S-24PD-L, 2960S-24PS-L, 2960S-24TD-L, 2960S-24TS-L, 2960S-24TS-S, 2960S-48FPD-L, 2960S-48FPS-L, 2960S-48LPD-L, 2960S-48LPS-L, 2960S-48TD-L, 2960S-48TS-L, 2960S-48TS-S, 3560E-24PD, 3560E-24TD, 3560E-48PD, 3560E-48PD-F, 3560E-48TD, 3560E-48TD-SD, 3560V2-24PS, 3560V2-24TS, 3560V2-24TS-SD, 3560V2-48PS, 3560V2-48TS, 3750E-24PD, 3750E-24TD, 3750E-48PD, 3750E-48PD-F, 3750E-48TD
---------------	---

Environmental Parameters

Min Operating Temperature:	-5 °C
Max Operating Temperature:	45 °C
Humidity Range Operating:	10 - 85%

Dimensions & Weight

Width:	15.2 cm
Depth:	29 cm
Height:	4.2 cm
Weight:	1.8 kg