

Cisco TelePresence ISDN Link, encrypted version - ISDN terminal adapter



Not in stock

SKU	CTS-ISDNLINK-K9
Product Description:	Cisco TelePresence ISDN Link, encrypted version - ISDN terminal adapter
Device Type:	ISDN terminal adapter
Form Factor:	External
Max Transfer Rate:	1920 Kbps
Digital Signaling Protocol:	H.239
Data Compression Protocol:	G.711, G.722, H.261, H.263, H.264, H.263++, G.722.1
Power:	AC 100/230 V (50/60 Hz)



General

Device Type:	ISDN terminal adapter
Form Factor:	External

Modem

Connectivity Technology:	Wired
Max Transfer Rate:	1920 Kbps
Digital Signaling Protocol:	H.239
Data Compression Protocol:	G.711, G.722, H.261, H.263, H.264, H.263++, G.722.1
Features:	Wall mountable

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	35 °C
Humidity Range Operating:	10 - 90%

Dimensions & Weight

Width:	28 cm
Depth:	17 cm
Height:	3 cm

Manufacturer Warranty

Service & Support:	Limited warranty - 90 days
--------------------	----------------------------

Power

Voltage Required:	AC 100/230 V (50/60 Hz)
-------------------	-------------------------

Miscellaneous

Cables Included:	1 x network cable
Included Accessories:	Power adapter

Expansion / Connectivity

Interfaces:	4 x ISDN BRI ST - RJ-45 ; 1 x modem - ISDN PRI E1/T1 - RJ-45 ; 1 x network - RS-366/449//530/V.35 - RJ-45 ; 2 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45
-------------	---

