

Cisco UCS C220 M3 High-Density Rack-Mount Server Small Form Factor - rack-mountable - no CPU - 0 GB - no HDD



Not in stock

SKU	UCSC-C220-M3S=
Product Description:	Cisco UCS C220 M3 High-Density Rack-Mount Server Small Form Factor - rack-mountable - no CPU - 0 GB - no HDD
Type:	Server - rack-mountable
Height (Rack Units):	1U
Server Scalability:	2-way
Processor:	No CPU
Processor Socket:	LGA2011 Socket
RAM:	0 GB DDR3 SDRAM - ECC

General

Type:	Server
Product Form Factor:	Rack-mountable - 1U
Server Scalability:	2-way
Hot-Swap Bays Qty:	8

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 90% (non-condensing)

Processor / Chipset

CPU:	No CPU
Max CPU Qty:	2
CPU Upgradability:	Upgradable
CPU Socket:	LGA2011 Socket
Chipset Type:	Intel C600

Dimensions & Weight

Width:	43 cm
Depth:	72.4 cm
Height:	4.3 cm
Weight:	10 kg

RAM

Installed Size:	0 GB
Technology:	DDR3 SDRAM - ECC
Features:	Registered, Memory Mirroring, low-voltage

Manufacturer Warranty

Service & Support:	Limited warranty - replacement - 3 years - response time: next business day
--------------------	---

Hard Drive

Type:	No HDD
-------	--------

Power

Device Type:	Power supply
Power Redundancy:	Optional

Storage Controller

Type:	1 x RAID - integrated
Controller Interface Type:	SATA 3Gb/s
Channel Qty:	4
RAID Level:	RAID 0, RAID 1, RAID 10

Optical Storage

Type:	No optical drive
-------	------------------

Monitor

Monitor Type:	None.
---------------	-------

Graphics Controller

Type:	Integrated
Graphics Processor:	Matrox G200e
Video Memory:	256 MB
Video Interfaces:	VGA

Networking

Type:	Integrated
Ethernet Ports:	2 x Gigabit Ethernet
Ethernet Controller:	Intel I350
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol:	IPMI 2.0, CLI

Power

Power Redundancy Scheme:	1+1 (with optional power supply)
Installed Qty:	0
Max Supported Qty:	2
Voltage Required:	AC 120/230 V (50/60 Hz)

Miscellaneous

Included Accessories:	Rack rail kit
Compliant Standards:	CISPR 22 Class A, BSMI CNS 13438 Class A, CISPR 24, EN 61000-3-2, VCCI Class A ITE, EN 61000-3-3, EN55024, EN55022 Class A, AS/NZS 60950-1, ICES-003 Class A, FCC CFR47 Part 15, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60950-1, GB 4943, EN 300 386

Expansion / Connectivity

Bays:	8 (total) / 8 (free) x hot-swap 2.5"
Slots:	2 (total) / 2 (free) x CPU ; 16 (total) / 16 (free) x memory ; 1 (total) / 1 (free) x PCIe 2.0 x8 - half-length ; 1 (total) / 1 (free) x PCIe 2.0 x16 - half-length, full-height
Interfaces:	1 x serial ; 2 x USB 2.0 ; 1 x management (NIC) ; 1 x VGA ; 2 x LAN (Gigabit Ethernet) ; 1 x KVM

